BioLAB

PRODUCT CATALOG



BIOCHEMICAL INCUBATOR BGE-304

CE ISO9001 CERTIFIED

www.biolabscientific.com

COOLING INCUBATOR BGE-304

BIOCHEMICAL INCUBATOR



The shell is made of cold-rolling steel with static spray plastics, the working chamber is made of mirror stainless steel, the shelves can be adjusted optionally;
PMMA II operating system, with over temperature alarm and self -diagnosis function;
Color LCD b acklight display
With screen lock time, screen saver password setting function, to prevent operation at will;
Programmable design, it c an be se t 30 segments 99 cycles;
Use centrifugal fan t o make the temperature of the working room uniform and stable;
Observation glass inner door ;

SPECIFICATIONS

Model	BGE-304
Capacity	400 L
Temperature Range	0-70°C
Temperature Accuracy	
Temperature Resolution	0.1°C
Temperature Fluctuation	±0.5°C Heating, ±0.7°C Cooling
Temperature Uniformity at 37°C	±1°C
Type	Biochemical / Mould Incubator
Power	1350 W
Timer Range (min/h)	0-9999
Reservation Range (min)	0-9999
Internal Dimensions (W*D*H)	600*640*1050mm
External Dimensions (W*D*H)	745*930*1695mm
Shelves (Standard/Maximum)	4/7
Load per Shelf	15 kg
Net/Gross Weight	150/208 kg
Package Size (mm)	860x1060x1880
Alt Name	Biochemical Incubator









FEATURES

The shell is made of cold-rolling steel with static spray plastics, the working chamber is made of mirror stainless steel, the shelves can be adjusted optionally;
PMMA II operating system, with over temperature alarm and self -diagnosis function;
Color LCD b acklight display

With screen lock time, screen saver password setting function, to prevent operation at will;
Programmable design, it c an be se t 30 segments 99 cycles;
Use centrifugal fan t o make the temperature of the working room
uniform and stable;
Observation glass inner door ;
Test holes are equipped on both sides, internal diameter is 30mm;
The fan has 6-stage speed regulation,
With reservation and timing func tion;
Equipped with mechanical lock ;
Equipped with 220V power sock et;
Equipped with fluorescent lamp in working chamber (mould incubator is equipped with UV light);
Adopt imported compressor unit , low noise, s table perf ormance;
Power supply r ecover y func tion, da ta will no t be los t when power failure
and system halted.

Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com