BioLAB

PRODUCT CATALOG



# MOLD AND FUNGAL INCUBATOR BGE-601

CE ISO9001 CERTIFIED

www.biolabscientific.com

# MOLD AND FUNGAL INCUBATOR BGE-601

MOLD INCUBATOR



The shell is made of cold-rolling steel with static spray plastics, the working chamber is
made of mirror stainless steel, the shelves can be adjusted op tionally;
PMMA II operating system, with over temperature alarm and self -diagnosis func tion;
The fan has 6-stage speed regulation, which can meet the different requirements
8W fluorescent lamp in working chamber (mould incubator is equipped with 8W UV light);
Large vie wing angle he at preservation vacuum toughened glass is convenient f or users t o observe;
Equipped with 220V power socket;
Frequency conversion refrigeration system, environmental protection refrigerant

## SPECIFICATIONS

| Model | BGE-601 |
|---|---|
| Capacity | 100L |
| Temperature Range | 0-60°C |
| Temperature Accuracy | |
| Type | Biochemical / Mould Incubator |
| Internal Dimensions (W*D*H) | 500x370x580mm |
| External Dimensions (W*D*H) | 580x570x1070mm |
| Temperature Resolution (°C) | 0.1 |
| Temperature Fluctuation (°C) | ±0.7 Heating / ±1 Cooling |
| Temperature Uniformity at 37°C (°C) | ±1.5 |
| Power (W) | 500 |
| Timer Range | 0-9999 min/h |
| Number of Shelves (Standard/Max.) | 2/3 |
| Load per Shelf (kg) | 15 |
| Net/Gross Weight (kg) | 70/110 |
| Package Size (mm) | 700x660x1400 |
| Alt Name | Mold Incubator |

## FEATURES

The shell is made of cold-rolling steel with static spray plastics, the working chamber is
made of mirror stainless steel, the shelves can be adjusted op tionally;
PMMA II operating system, with over temperature alarm and self -diagnosis func tion;
The fan has 6-stage speed regulation, which can meet the different requirements
8W fluorescent lamp in working chamber (mould incubator is equipped with 8W UV light);
Large vie wing angle he at preservation vacuum toughened glass is convenient f or users t o observe;
Equipped with 220V power socket;
Frequency conversion refrigeration system, environmental protection refrigerant (R134a),
high efficiency, low ener gy consumption, full temperature continuous fr ost-free operation;
Adopt import ed compressor unit , low noise, s table perf ormance;
Power supply r ecovery func tion, da ta will no t be los t when power failure and sys tem halt ed



Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com