BioLAB

PRODUCT CATALOG



MOLD AND FUNGAL INCUBATOR BGE-602

CE ISO9001 CERTIFIED

www.biolabscientific.com

MOLD AND FUNGAL INCUBATOR BGE-602

MOLD INCUBATOR



The shell is made of cold-rolling steel with static spray plastics, the working chamber is
made of mirror stainless steel, the shelves can be adjusted op tionally;
PMMA II operating system, with over temperature alarm and self -diagnosis func tion;
The fan has 6-stage speed regulation, which can meet the different requirements
8W fluorescent lamp in working chamber (mould incubator is equipped with 8W UV light);
Large vie wing angle he at preservation vacuum toughened glass is convenient f or users t o observe;
Equipped with 220V power socket;
Frequency conversion refrigeration system, environmental protection refrigerant

SPECIFICATIONS

Model	BGE-602
Capacity	150L
Temperature Range	0-60℃
Temperature Accuracy	
Type	Biochemical / Mould Incubator
Internal Dimensions (W*D*H)	500x370x815mm
External Dimensions (W*D*H)	595x580x1232mm
Temperature Resolution (℃)	0.1
Temperature Fluctuation (℃)	±0.7 Heating / ±1 Cooling
Temperature Uniformity at 37℃ (℃)	±1.5
Power (W)	500
Timer Range	0-9999 min/h
Number of Shelves (Standard/Max.)	3/5
Load per Shelf (kg)	15
Net/Gross Weight (kg)	82/114
Package Size (mm)	700x660x1490
Alt Name	Mold Incubator

FEATURES

The shell is made of cold-rolling steel with static spray plastics, the working chamber is
made of mirror stainless steel, the shelves can be adjusted op tionally;
PMMA II operating system, with over temperature alarm and self -diagnosis func tion;
The fan has 6-stage speed regulation, which can meet the different requirements
8W fluorescent lamp in working chamber (mould incubator is equipped with 8W UV light);
Large vie wing angle he at preservation vacuum toughened glass is convenient f or users t o observe;
Equipped with 220V power socket;
Frequency conversion refrigeration system, environmental protection refrigerant (R134a),
high efficiency, low ener gy consumption, full temperature continuous fr ost-free operation;
Adopt import ed compressor unit , low noise, s table perf ormance;
Power supply r ecovery func tion, da ta will no t be los t when power failure and sys tem halt ed



Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com