BioLAB

PRODUCT CATALOG



# MOLD AND FUNGAL INCUBATOR BGE-701

CE ISO9001 CERTIFIED

www.biolabscientific.com

# MOLD AND FUNGAL INCUBATOR BGE-701

MOLD INCUBATOR



The shell is made of c old-rolling s teel with s tatic spr ay plas tics, the working chamber is made of mirror stainless steel, the shelves can be adjusted optionally;
PAMMA II control sys tem, L CD screen displays temperature and time, over -temperature alarm function;
Use centrifugal fan to make the temperature of the working room uniform and stable
Double door design, observation glass inner door ;
Test holes are equipped on both sides, internal diameter is 30mm;
Well-known international brand compressor, non-CF C refrigerant
Equipped with mechanical lock ,
Integrated type refrigeration sys tem,

## SPECIFICATIONS

| Model | BGE-701 |
|---|---|
| Capacity | 100L |
| Temperature Range | 0-70°C |
| Temperature Accuracy | |
| Type | Biochemical / Mould Incubator |
| Temperature Resolution (°C) | 0.1 |
| Temperature Fluctuation (°C) | ±0.5 Heating / ±0.7 Cooling |
| Temperature Uniformity at 37°C (°C) | ±1 |
| Power (W) | 1000 |
| Timer Range (min/h) | 0-9999 |
| Reservation Range (min) | 0-9999 |
| Internal Dimensions (W*D*H) | 490*390*610mm |
| External Dimensions (W*D*H) | 630*680*1250mm |
| Number of Shelves (Standard/Max.) | 2/4 |
| Load per Shelf (kg) | 15 |
| Net/Gross Weight (kg) | 91/129 |
| Package Size (mm) | 730x820x1440 |
| Alt Name | Mold incubator |









## FEATURES

The shell is made of c old-rolling s teel with s tatic spr ay plas tics, the working chamber is made of mirror stainless steel, the shelves can be adjusted optionally;
PAMMA II control sys tem, L CD screen displays temperature and time, over -temperature alarm function;
Use centrifugal fan to make the temperature of the working room uniform and stable

Double door design, observation glass inner door ;
Test holes are equipped on both sides, internal diameter is 30mm;
Well-known international brand compressor, non-CF C refrigerant
Equipped with mechanical lock ,
Integrated type refrigeration sys tem,
Imported humidity sensor , electric heating humidification sys tem,
large capacity w ater t ank;
Programmable design, it c an be se t 30 segments 99 cycles;
Power supply recover y func tion, da ta will no t be los t when power failure and system halted.

Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com