BioLAB

PRODUCT CATALOG

MOLD AND FUNGAL INCUBATOR BGE-704



CE ISO9001 CERTIFIED

www.biolabscientific.com

MOLD AND FUNGAL INCUBATOR BGE-704

MOLD INCUBATOR

The shell is made of c old-rolling s teel with s tatic spr ay plas tics, the working chamber is made of mirror stainless steel, the shelves can be adjusted optionally;
PAMMA II control sys tem, L CD screen displays temperature and time, over -temperature alarm function;
Use centrifugal fan to make the temperature of the working room uniform and stable
Double door design, observation glass inner door ;
Test holes are equipped on both sides, internal diameter is 30mm;
Well-known international brand compressor, non-CF C refrigerant
Equipped with mechanical lock ,
Integrated type refrigeration sys tem,

SPECIFICATIONS

Model	BGE-704
Capacity	400L
Temperature Range	0-70°C
Temperature Accuracy	
Type	Biochemical / Mould Incubator
Temperature Resolution (°C)	0.1
Temperature Fluctuation (°C)	±0.5 Heating / ±0.7 Cooling
Temperature Uniformity at 37°C (°C)	±1
Power (W)	1350
Timer Range (min/h)	0-9999
Reservation Range (min)	0-9999
Internal Dimensions (W*D*H)	600*640*1050mm
External Dimensions (W*D*H)	745*930*1695mm
Number of Shelves (Standard/Max.)	4/7
Load per Shelf (kg)	15
Net/Gross Weight (kg)	150/208
Package Size (mm)	860x1060x1880
Alt Name	Mold incubator

FEATURES

The shell is made of c old-rolling s teel with s tatic spr ay plas tics, the working chamber is made of mirror stainless steel, the shelves can be adjusted optionally;
PAMMA II control sys tem, L CD screen displays temperature and time, over -temperature alarm function;
Use centrifugal fan to make the temperature of the working room uniform and stable
Double door design, observation glass inner door ;
Test holes are equipped on both sides, internal diameter is 30mm;
Well-known international brand compressor, non-CF C refrigerant
Equipped with mechanical lock ,
Integrated type refrigeration sys tem,
Imported humidity sensor , electric heating humidification sys tem,
large capacity w ater t ank;
Programmable design, it c an be se t 30 segments 99 cycles;
Power supply recover y func tion, da ta will no t be los t when power failure and system halted.



Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com