BioLAB

PRODUCT CATALOG

# MOLD AND FUNGAL INCUBATOR BGE-905



CE ISO9001 CERTIFIED

www.biolabscientific.com

# MOLD AND FUNGAL INCUBATOR BGE-905

MOLD INCUBATOR

·5-inch LCD touch screen;
·BRIGHT I control system;
·Programmed multi segment parameter settings: 30 segment 99 cycle design;
·Can store data for more than 10 years (non SD card storage);
·Multi-level password management;
·Equipped with appointment timing func tion;
·The fan has 6-stage speed regulation;
·Double door design, observation glass inner door ;
·Variable frequency refrigeration, imported compressor ;
·Equipped with one U SB interface and two R S-485 interfaces;
·Equipped with mechanical lock ;
·Test holes are equipped on both sides, internal diameter is 30mm;

## SPECIFICATIONS

| Model | BGE-905 |
|---|---|
| Capacity | 1000L |
| Temperature Range | 0-80℃ |
| Temperature Accuracy | |
| Power Supply | AC 220V ±10V, 50/60Hz |
| Ambient Temperature (℃) | 10-30 |
| Temperature Resolution (℃) | 0.1 |
| Temperature Fluctuation (℃) | ±0.3 Heating / ±0.5 Cooling |
| Temperature Uniformity at 25℃ (℃) | ±0.8 |
| Power (W) | 1500 |
| Timer Range (min/h) | 0-9999 |
| Internal Dimensions (W*D*H) | 1363x670x1123mm |
| External Dimensions (W*D*H) | 1505x1006x1811mm |
| Number of Shelves (Standard/Max.) | 6/12 |
| Load per Shelf (kg) | 15 |
| Net/Gross Weight (kg) | 340/430 |
| Package Size (mm) | 1640x1180x2040 |
| Alt Name | Mold Incubator |

## FEATURES

·5-inch LCD touch screen;
·BRIGHT I control system;
·Programmed multi segment parameter settings: 30 segment 99 cycle design;
·Can store data for more than 10 years (non SD card storage);
·Multi-level password management;
·Equipped with appointment timing func tion;
·The fan has 6-stage speed regulation;
·Double door design, observation glass inner door ;
·Variable frequency refrigeration, imported compressor ;
·Equipped with one U SB interface and two R S-485 interfaces;
·Equipped with mechanical lock ;
·Test holes are equipped on both sides, internal diameter is 30mm;
·Equipped with 220V power socket;
·8W fluorescent lamp in working chamber ;
·Over temperature alarm, over temperature shut down protection, door open alarm, sensor fault alarm, overload

protection, leakage protection, compressor over temperature protection;
·Optional: online monitoring platform, GPR S SMS alarm,printer.

Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com