



MINI DRY BATH INCUBATOR BGH1E3 (BDMI-109)

MINI DRY BATH INCUBATOR BGH1E3

MINI-DRY BATH INCUBATOR



Small footprint: They are a personal size that fits in the palm on your hand; light weight, less than 1 kg.
DC 12V or DC 24V power input, built-in over temperature protection device, suitable for car power supply.
Temperature deflection adjusting meets with different demands.
Interchangeable aluminum alloy sample blocks provide versatility and allow easy cleaning and disinfecting.

SPECIFICATIONS

Model	BGH1E3
Old Model	BDMI-109
Temperature control range	RT. +5 °C~100 °C
Timer range	1-999 min or 1-999 sec
Temp. control accuracy	±0.5 °C
Display accuracy	±0.1 °C
Heating time (25 °C to max.)	≤15 min
Cooling time (20 °C to 0 °C)	/
Temp. stability	±0.3 °C
Thermo lid	/
Thermo lid temp. control range	/
Dimension (LxWxH) mm	152x120x112
Weight	0.8 kg
Power supply	DC 24 V
Alt Name	Mini-Dry Bath Incubator

ACCESSORIES FOR PURCHASE

No	Name	Type	Description
1	Block	AMini-T	40x0.2 mL tube
2	Block	BMini-T	24x0.5 mL tube
3	Block	CMini-T	15x1.5 mL tube
4	Block	DMini-T	15x2.0 mL tube
5	Block	EMini-T	8x12.5x12.5 mL cuvette block
6	Block	FMini-T	4x15 mL tube
7	Block	GMini-T	2x50 mL tube
8	Block	Can be customized	



1



2



3



4



5



6



7

FEATURES

Small footprint: They are a personal size that fits in the palm on your hand; light weight, less than 1 kg.
DC 12V or DC 24V power input, built-in over temperature protection device, suitable for car power supply.
Temperature deflection adjusting meets with different demands.
Interchangeable aluminum alloy sample blocks provide versatility and allow easy cleaning and disinfecting.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com