



OIL BATH CIRCULATOR BGI-3902

OIL BATH CIRCULATOR BGI-3902

HEATING OIL BATH

Corrosion resistant stainless steel with microprocessor controller heating oil bath, provides you best security and stability, and easy to operate.



- PID controller with timing function ensures precise and reliable control.
- Stainless steel working chamber and shell, anti-corrosion and easy to clean.
- Audible and visible alarm for temperature ensures experiments run safely.
- Magnetic stirring oil bath with microcomputer servo control of stirring speed, to ensure the constant speed in the case of constantly changing stirring viscosity.
- Magnetic stirring output torque is large, making the temperature in the oil bath more accurate and uniform.

Option:

Intelligent programmable LCD temperature controller
RS485 connector

SPECIFICATIONS

Model	BGI-3902
Electrical Requirement	AC220V 50HZ
Power	1000W
Temperature Range	RT+20~200°C
Temperature Stability	±0.5°C
Deviation Alarm	±2°C
Volume	12L
Interior Dimension (WxHxD,mm)	250x250x200
Timer Range	0~9999
Packing Dimension	55*50*42
CBM	0.12
Net Weight	12.00
Gross weight	15
Alt Name	Heating Oil Bath



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com