



## MAGNETIC STIRRER BGI-4609

# MAGNETIC STIRRER BGI-4609

## MAGNETIC STIRRER

LCD Microprocessor Controller (with timing function)

The BEING Magnetic Heated Stirrers offer a large variety of sizes and temperature ranges to accommodate your laboratory needs. Our stirrers provide a user friendly PID controller offering a large LCD color screen for easy viewing. They are constructed for durability, high performance and safety.



- Large LCD screen to display more data at same time.
- External temperature sensor for liquid, temperature range from ambient temperature to 200°C .
- Free-step speed adjustment.
- Die-cast Aluminum alloy external chamber.
- Aluminum alloy working plate.
- Over-temp alarm system, auto switch off when 470°C .
- Caution indication light when plate temperature reach 50°C .
- These Magnetic Stirrer include external temperature sensor which can measure liquid's temperature directly. Temperature range is from Ambient +5°C to 200°C .

## SPECIFICATIONS

Model	BGI-4609
Stirring capacity (H <sub>2</sub> O)	3L
Speed range (rpm)	100~1600 (Optional 2000)
Power	600W
Liquid temp range	RT+5 ~ 200°C
Working plate temp range	-
Temperature accuracy	±1°C
Plate dimension (mm)	Φ145
Exterior dimension (WxHxD) mm	155x120x250
Weight (KG)	
Alt Name	Magnetic Stirrer



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)