



MAGNETIC STIRRER BGI-4610

MAGNETIC STIRRER BGI-4610

MAGNETIC STIRRER

LCD Microprocessor Controller (with timing function)

The BEING Magnetic Heated Stirrers offer a large variety of sizes and temperature ranges to accommodate your laboratory needs. Our stirrers provide a user friendly PID controller offering a large LCD color screen for easy viewing. They are constructed for durability, high performance and safety.



- Large LCD screen to display more data at same time.
- External temperature sensor for liquid, temperature range from ambient temperature to 200°C .
- Free-step speed adjustment.
- Die-cast Aluminum alloy external chamber.
- Aluminum alloy working plate.
- Over-temp alarm system, auto switch off when 470°C .
- Caution indication light when plate temperature reach 50°C .
- These Magnetic Stirrer are able to reach highest temperature as 320°C .

SPECIFICATIONS

Model	BGI-4610
Stirring capacity (H ₂ O)	3L
Speed range (rpm)	100~1600 (Optional 2000)
Power	600W
Liquid temp range	/
Working plate temp range	RT+5 ~ 320°C
Temperature accuracy	±1°C
Plate dimension (mm)	Φ145
Exterior dimension (WxHxD) mm	155x120x250
Weight (KG)	3.5
Alt Name	Magnetic Stirrer



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com