



STABILITY TEST CHAMBER BGI1BH2 (BTST-1602)

STABILITY TEST CHAMBER BGI1BH2

LARGE MEDICINE STABILITY TESTING CHAMBER



SPECIFICATIONS

Model	BGI1BH2
Old Model	BTST-1602
Temperature control range	0~65°C
Temperature Stability	±0.5°C
Temperature Uniformity	±2°C ~ ±3°C
Humidity Range	35~95%RH
Humidity Stability	±3%RH
Illumination	/
Illumination difference	/
Cooling systemcooling mode	Two sets of Imported compressor work rotationally
Controller	Programmable (touch screen)
Sensor	Temp: Pt100, Humidity: capacitance sensor
Ambient Temperature	RT+5~30°C
Electrical Requirement	AC220V 50Hz
Power Consumption	3750W
Operating Power	1400W
Chamber Volume	500L
Interior Dimension (WxDxH,mm)	670x725x1020
External Dimension (WxDxH,mm)	850x1100x1930
Shelves	4(pcs)
Safety Device	Compressor overheating and overpressure protection, Fan overheating protection, Over temperature protection, Overload protection, Water protections
Remark	1. Build in mini printer2. Paperless recorder (Option)
Alt Name	Large Medicine Stability Testing Chamber



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com