



STABILITY TEST CHAMBER BGI1BH5 (BTST-1605)

STABILITY TEST CHAMBER BGI1BH5

LARGE MEDICINE STABILITY TESTING CHAMBER



SPECIFICATIONS

Model	BGI1BH5
Old Model	BTST-1605
Temperature control range	0~65°C
Temperature Stability	±0.5°C
Temperature Uniformity	±2°C ~ ±3°C
Humidity Range	35~95%RH
Humidity Stability	±3%RH
Illumination	/
Illumination difference	/
Cooling systemcooling mode	Two sets of Imported compressor work rotationally
Controller	Programmable (touch screen)
Sensor	Temp: Pt100, Humidity: capacitance sensor
Ambient Temperature	RT+5~30°C
Electrical Requirement	AC220V 50Hz
Power Consumption	3500W
Operating Power	2800W
Chamber Volume	1000L
Interior Dimension (WxDxH,mm)	1050x590x1650
External Dimension (WxDxH,mm)	1610x890x2000
Shelves	4(pcs)
Safety Device	Compressor overheating and overpressure protection, Fan overheating protection, Over temperature protection, Overload protection, Water protections
Remark	1. Build in mini printer2. Paperless recorder (Option)3. 1000L and 1500L are double doors
Alt Name	Large Medicine Stability Testing Chamber



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com