



## OIL BATH CIRCULATOR BGI1BN3 (BCOB-202)

# OIL BATH CIRCULATOR BGI1BN3

## HEATING OIL BATH

Corrosion resistant stainless steel with microprocessor controller heating oil bath, provides you best security and stability, and easy to operate.



- PID controller with timing function ensures precise and reliable control.
- Stainless steel working chamber and shell, anti-corrosion and easy to clean.
- Audible and visible alarm for temperature ensures experiments run safely.
- Magnetic stirring oil bath with microcomputer servo control of stirring speed, to ensure the constant speed in the case of constantly changing stirring viscosity.
- Magnetic stirring output torque is large, making the temperature in the oil bath more accurate and uniform.

Option:

Intelligent programmable LCD temperature controller  
RS485 connector

## SPECIFICATIONS

Model	BGI1BN3
Old Model	BCOB-202
Electrical Requirement	AC220V 50HZ
Power	1600W
Temperature Range	RT+20~200°C
Temperature Stability	±0.5°C
Deviation Alarm	±2°C
Volume	20L
Interior Dimension (WxHxD,mm)	400x250x200
Timer Range	0~9999
Alt Name	Heating Oil Bath



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)