



WATER BATH BGI1BR3 (BCHT-3301)

WATER BATH BGI1BR3

CIRCULATING BATH, WATER BATH



Microprocessor controller (with timing function)

- Microprocessor control with timing function.
- Digital display.
- Audible and visible alarm for over temperature.

SPECIFICATIONS

Model	BGI1BR3
Old Model	BCHT-3301
Electrical Requirement	220V 50Hz
Power Consumption	1000W
Temperature Range	RT+5~70°C
Temperature Stability	±0.3°C
Display Resolution	0.1°C
Chamber Volume	22L
Interior Dimension (WxDxH, mm)	500x300x150
Exterior Dimension (WxDxH, mm)	620x340x260
Timing Range	1~9999min
Alt Name	Circulating Bath (with electromagnetic-pump)

ACCESSORIES FOR PURCHASE

No	Name
1	Intelligent programmable temperature controller
2	RS485 connector




1



1



2



2

APPLICATIONS

Provided for precise and constant temperature and auxiliary heating in colleges industrial and mining enterprises and scientific research departments.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com