



WATER BATH BGI1BR4 (BCHT-3302)

WATER BATH BGI1BR4

CIRCULATING BATH, WATER BATH



Microprocessor controller (with timing function)

- Microprocessor control with timing function.
- Digital display.
- Audible and visible alarm for over temperature.

SPECIFICATIONS

Model	BGI1BR4
Old Model	BCHT-3302
Electrical Requirement	220V 50Hz
Power Consumption	1000W
Temperature Range	RT+5~70°C
Temperature Stability	±0.3°C
Display Resolution	0.1°C
Chamber Volume	30L
Interior Dimension (WxDxH, mm)	600x300x190
Exterior Dimension (WxDxH, mm)	770x370x280
Timing Range	1~9999min
Alt Name	Circulating Bath (with electromagnetic-pump)

ACCESSORIES FOR PURCHASE

No	Name
1	Intelligent programmable temperature controller
2	RS485 connector




1



1



2



2

APPLICATIONS

Provided for precise and constant temperature and auxiliary heating in colleges industrial and mining enterprises and scientific research departments.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com