



WATER BATH BGI1BR7 (BBWA-3203)

WATER BATH BGI1BR7

CIRCULATING BATH, WATER BATH



Microprocessor controller (with timing function)

- Microprocessor control with timing function.
- Digital display.
- Audible and visible alarm for over temperature.

SPECIFICATIONS

Model	BGI1BR7
Old Model	BBWA-3203
Electrical Requirement	220V 50Hz
Power Consumption	1000W
Temperature Range	RT+5~100°C
Temperature Stability	±0.5°C
Display Resolution	0.1°C
Chamber Volume	28.8L
Interior Dimension (WxDxH, mm)	600x300x160
Exterior Dimension (WxDxH, mm)	760x340x280
Timing Range	1~9999min
Alt Name	Water Bath (all stainless steel)

ACCESSORIES FOR PURCHASE

No	Name
1	Intelligent programmable temperature controller
2	RS485 connector




1



1



2



2

APPLICATIONS

Provided for precise and constant temperature and auxiliary heating in colleges industrial and mining enterprises and scientific research departments.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com