



WATER BATH BGI1BR8 (BBWA-3206)

WATER BATH BGI1BR8

CIRCULATING BATH, WATER BATH



Microprocessor controller (with timing function)

- Microprocessor control with timing function.
- Digital display.
- Audible and visible alarm for over temperature.

SPECIFICATIONS

Model	BGI1BR8
Old Model	BBWA-3206
Electrical Requirement	220V 50Hz
Power Consumption	750W
Temperature Range	RT+5~99°C
Temperature Stability	±0.3°C
Display Resolution	0.1°C
Chamber Volume	2.1Lx3
Interior Dimension (WxDxH, mm)	162x149x151
Exterior Dimension (WxDxH, mm)	505x245x350
Timing Range	1~9999min
Alt Name	Water Bath (three holes)

ACCESSORIES FOR PURCHASE

No	Name
1	Intelligent programmable temperature controller
2	RS485 connector




1



1



2



2

APPLICATIONS

Provided for precise and constant temperature and auxiliary heating in colleges industrial and mining enterprises and scientific research departments.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com