



VACUUM OVEN BGI1I2 (BOVA-7302)

VACUUM OVEN BG11I2

VACUUM OVEN

Microprocessor controller (with timing function)

Vacuum oven is designed especially for drying of material which is thermo-sensitive or decomposes and oxidative easily. It can be filled with inert gases, which is especially for a rapid drying of some compound material.



- Microprocessor controller.
- Dual layer tempered glass door for clear observation.
- Minimum heating time 50% less than traditional vacuum oven.
- Interior chamber made from stainless steel with a mirror polished finish making for easy cleaning.
- Standard with vacuum pump.
- Direct heating and control by shelves: Each shelf has a separate temperature sensor, can be independently displayed and controlled temperature in setting, monitoring and timing, more accurate and stable

SPECIFICATIONS

Model	BG11I2
Old Model	BOVA-7302
Electrical Requirement	AC380V 50HZ
Controller	LED display
Power Consumption	3800W
Temperature Range	RT+10 ~ 200°C
Display Resolution	0.1
Temperature Stability	±1°C
Vacuum Degree	133Pa
Ambient Temperature	+5~40°C
Chamber Volume	431L
Interior Dimension (WxDxH) mm	630x810x845
Exterior Dimension (WxDxH) mm	1000x1040x1855
Shelves	4pcs (Independent temp. control)
Chamber Material	304 Stainless steel
Alt Name	Vacuum Oven





Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com