





GENERAL PURPOSE INCUBATOR BGI1011 (BIGP-206)





GENERAL PURPOSE INCUBATOR BGI1011

HEATING INCUBATOR

Microprocessor Controller (with timing function)

Provided as a necessary equipment for scientific research to colleges as well as biological, agricultural and scientific research departments for storage of mould and biology cultivation.



- With inner glass door for easy observation.
- Polished stainless-steel chamber.
- Independent temperature-limiting alarm system ensures experiments run safely.(Option)
- Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature.(Option) Options:
- Printer
- Independent temperature-limiting Alarm system
- RS485 connector
- UV Sterilizer

SPECIFICATIONS

Model	BG 1011
Old Model	BIGP-206
Electrical Requirement	220V 50Hz
Temperature Range	RT+5~65°C
Display Resolution	0.1℃
Ambient Temperature	+5~35°C
Temperature Uniformity	±1.5°C (at 37°C)
Power Consumption	750W
Chamber Volume	270L
Interior Dimension (WxDxH) mm	600x600x750
Exterior Dimension (WxDxH) mm	890x740x910
Shelves (pcs)	2
Timing Range	0-5999min
Remark	
Alt Name	Heating Incubator



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada Email: info@biolabscientific.com | Website: www.biolabscientific.com