



## GENERAL PURPOSE INCUBATOR BGI102 (BIGP-7601)

# GENERAL PURPOSE INCUBATOR BGI102

## HEATING INCUBATOR

Microprocessor Controller (with timing function)

Provided as a necessary equipment for scientific research to colleges as well as biological, agricultural and scientific research departments for storage of mould and biology cultivation.



- With inner glass door for easy observation.
  - Polished stainless-steel chamber.
  - Independent temperature-limiting alarm system ensures experiments run safely.(Option)
  - Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature.(Option)
- Options:
- Printer
  - Independent temperature-limiting Alarm system
  - RS485 connector
  - UV Sterilizer

## SPECIFICATIONS

Model	BGI102
Old Model	BIGP-7601
Electrical Requirement	220V 50Hz
Temperature Range	RT+5~65°C
Display Resolution	±0.5°C
Ambient Temperature	+5~35°C
Temperature Uniformity	±1.5°C (at 37°C)
Power Consumption	200W
Chamber Volume	16L
Interior Dimension (WxDxH) mm	250x260x250
Exterior Dimension (WxDxH) mm	530x480x420
Shelves (pcs)	2
Timing Range	0-5999min
Remark	with observation window and without Inner glass door.
Alt Name	Heating Incubator



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)