





# COOLED INCUBATOR BGI1U14 (BICL-403)





### **COOLED INCUBATOR BGI1U14**

#### COOLING INCUBATOR



Microprocessor control

- Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
- Latest PID controller
- R134a refrigerant, imported compressor
- Independent temperature-limiting alarm system ensures experiments run safely.(Option)
- Printer connector and RS485 connector are options which can connect printer and computer

to record the parameters and the variations of temperature.(Option)

• There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement.

#### **SPECIFICATIONS**

Model	BGI1U14
Old Model	BICL-403
Temperature Range	-40°C~65°C
Display Resolution	0.1℃
Temperature Stability	High Temp ±0.5°C / Low Temp ±1.0°C
Electrical Requirement	380V 50Hz
Ambient Temperature	+5°C~35°C
Power Consumption	6100W
Interior Dimension (WxDxH)mm	600x500x830
Exterior Dimension (WxDxH)mm	800x1160x1850
Shelves	3(pcs)
Timing Range	0~9999min
Alt Name	Cooling Incubator

#### **FEATURES**

Microprocessor control

- Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
- Latest PID controller
- R134a refrigerant, imported compressor
- Independent temperature-limiting alarm system ensures experiments run safely.(Option)
- Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature.(Option)
- There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement.

Option:

- Printer
- Independent temperature-limiting Alarm system
- RS485 connector

#### **APPLICATIONS**

Serve for preserve culture medium, serum, medicine as well as microorganism training and environmental testing etc.



## Biolab Scientific Ltd.