



ELECTRIC OPERATION TABLE BGY1BV1 (BOPT-104)

ELECTRIC OPERATION TABLE BGY1BV1

ELECTRIC OR TABLE

Biolab's electric operation table are cost effective, multi performance mobile operating table that meets the requirement of different surgeons. Easy-to-use electronic controls. Operation table equipped with a table top that rotates 180 degrees, and the chest plate, back plate, head plate, and leg plate on this table can all be easily adjusted, allowing for the ideal positioning of patients undergoing medical imaging tests.



Electro-hydraulic mode of operation is adopted. Two control modes (hand-held remote controller and panel) are available to control various movements. MCU processing is used

Self-locking function is provided to avoid false triggering

Quality stainless steel 304 is used for table support, base plate, column shield and rails on both sides of the table, easy for cleaning and sterilization. Console supports the use of cast aluminium parts, never rust

The mattress is wrapped with imported artificial leather. High-density memory sponge is formed in one piece, with no seam

Quality carbon steel plate is used for the table top, which is convenient for X-ray photography

AC and DC can use at the same time

SPECIFICATIONS

Model	BGY1BV1
Old Model	BOPT-104
Table Length	2000±100 mm
Table Width	520±20 mm
Height Adjustment	(700~1150) ±50 mm
Tilt (left)/Tilt (Right)	≥15°/≥15°
Trendelenburg/Rev.-Trend	≥20°/≥20°
Head board upwards	≥50°
Head board downwards	≥90°
Backboard upwards	≥70°
Backboard downwards	≥40°
Waist board lifting	100±20 mm
Leg board upwards	≥15°
Leg board downwards	≥90°
Leg board outwards	≥180°
Lumbar upper corner "^^"	≤150°
Lumbar lower corner "v"	≤110°
Horizontal and longitudinal movement	400±30 mm
Standard Accessories	A Pair of Shoulder/Waist Support, A pair of Arm Support, A pair of leg Plate, A screen
Main Voltage AC	220V±22V, 50Hz±1Hz
Input Power VA	400±10%
Alt Name	Electric OR table

FEATURES

Electro-hydraulic mode of operation is adopted. Two control modes (hand-held remote controller and panel) are available to control various movements. MCU processing is used

Self-locking function is provided to avoid false triggering

Quality stainless steel 304 is used for table support, base plate, column shield and rails on both sides of the table, easy for cleaning and sterilization. Console supports the use of cast aluminium parts, never rust

The mattress is wrapped with imported artificial leather. High-density memory sponge is formed in one piece, with no seam

Quality carbon steel plate is used for the table top, which is convenient for X-ray photography
AC and DC can use at the same time
It has the function of auto-restoration
The table top can sliding
Electric braking device, convenient for shifting the operating table
One press to "∧" or "∨"

APPLICATIONS

Medical unit, Surgery, Operation theatre, cardiovascular, pediatric, gynecology, abdominal, gall bladder, plastic surgery and more



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com