



STAINING SYSTEM BHM1O1 (BHTP-403)

STAINING SYSTEM BHM101

SLIDE STAINER



1. Full English color touch screen display, ATM-type operation mode. The operation is simple and easy to understand.
2. Multiple sets of programs are available for editing (non-sequential editing can be performed, and dyeing steps and time can be programmed arbitrarily)
3. Automatic drying temperature can be set. The temperature around the drying cylinder is uniform, and there is a water and gas overflow.
4. With automatic detection and automatic reset function.
5. Strong anti-interference ability and high degree of intelligence.
6. Automatically control the flushing water level. When the dyed hanging blue enters the washing tank, the water is automatically filled in the washing tank. When the hanging blue leaves the washing tank, the water injection is automatically stopped, and the water in the tank is drained.

SPECIFICATIONS

Model	BHM101
Old Model	BHTP-403
Editable programs	16 sets, programmable arbitrarily
Processing volume per cylinder	1000 ml
Loading capacity	65 pieces each time
Single-cylinder processing time	0~99 min 99 sec
Number of shaking adjustments	Adjustable
Stirring times	Adjustable
Drip residence time	0~300 sec, adjustable
Cylinder positions	14 cylinders (1 washing, 1 drying)
Drying temperature	0-85 °C, adjustable
Power supply	220V 50Hz ±10%
Power consumption	≤300 W
Net Weight	80 kg
Dimensions	1161x480x550 mm
Package Info	
--Packing	Wooden Case
--Gross Weight	110 kg
--Package Dimensions	1260x615x695 mm
Alt Name	Slide Stainer

FEATURES

1. Full English color touch screen display, ATM-type operation mode. The operation is simple and easy to understand.
2. Multiple sets of programs are available for editing (non-sequential editing can be performed, and dyeing steps and time can be programmed arbitrarily)
3. Automatic drying temperature can be set. The temperature around the drying cylinder is uniform, and there is a water and gas overflow.
4. With automatic detection and automatic reset function.
5. Strong anti-interference ability and high degree of intelligence.
6. Automatically control the flushing water level. When the dyed hanging blue enters the washing tank, the water is automatically filled in the washing tank. When the hanging blue leaves the washing tank, the water injection is automatically stopped, and the water in the tank is drained.
7. It has the function of locking cylinder protection
8. The drip residence time is adjustable. The dripping time can be adjusted according to the sample volume and ambient temperature to ensure the purity of the reagent

9. The number of running steps is 24 steps, (the same cylinder position can be run repeatedly)
10. Adopt international standard synchronous toothed belt drive, low noise, high temperature resistance, corrosion resistance, high transmission accuracy, with photoelectric positioning sensor, so that the positioning is more accurate and the service life is long.
11. Harmful gas purification treatment: protect the health of staff and prevent the working environment from pollution



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com