



TISSUE PROCESSOR BHTP-309

TISSUE PROCESSOR BHTP-309

AUTOMATIC TISSUE PROCESSOR



1. English menu, man-machine interaction, simple operation. Prompt judge and automatic processing in case of abnormal condition, which can prevent the tissue from being damaged.
2. Double-control heat without water
3. Based on different tissues, several running programs available for customers
4. Self-provided power supply can continue to operate for 4 to 6 hours during a power outage. The tissue protection cylinder can be automatically operated after a power outage. Does not contain heated paraffin. If the temperature of the heated wax cylinder does not reach the set temperature, the tissue will not enter the wax cylinder and return to the protection cylinder

SPECIFICATIONS

Model	BHTP-309
Number of tanks	12 tanks (3 wax cylinders in the end)
Capacity of single tank	1000 ml
Cylinder start dwell time	45~100 seconds
Basket capacity	60 specimens
Single-tank processing time	0~99 hours, arbitrarily set
Stirring times	0~5 times/minute (3 times/minute is best)
Net Weight	60 kg
Dimensions	1010*390*450 mm
Package Info	
--Packing	Wooden Case
--Gross Weight	85 kg
--Package Dimensions	1140*560*580 mm
Alt Name	Automatic Tissue Processor

ITEMS INCLUDED

No	Name	Unit
1	Reagent bottle	9 pcs
2	Tissue basket	1 pc
3	Exhaust pipe	1 pc
4	Tissue cassette	20 pcs
5	Fuse (5A)	2 pcs
6	Power line	1 line

ACCESSORIES FOR PURCHASE

No	Name
1	Extra Tank
2	Tissue basket

FEATURES

1. English menu, man-machine interaction, simple operation. Prompt judge and automatic processing in case of abnormal condition, which can prevent the tissue from being damaged.
2. Double-control heat without water
3. Based on different tissues, several running programs available for customers
4. Self-provided power supply can continue to operate for 4 to 6 hours during a power outage. The tissue protection cylinder can be automatically operated after a power outage. Does not contain heated paraffin. If the temperature of the heated wax cylinder does not reach the set temperature, the tissue will not enter the wax cylinder and return to the protection cylinder to wait. High degree of intelligence
5. Environment friendly: The air as purified through internal circulation can be exhausted off the window.
6. With transmission of gear and rack, mechanical failures can be reduced.
7. With 16 sets of editable programs, intelligent operation and operation.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com