



PRINTING SYSTEM BHTP-503

PRINTING SYSTEM BHTP-503

COVER SLIPPER



1. Covers of various brands and specifications
2. Color touch screen control interface, real-time dynamic prompts of operation instructions, simple and efficient operation, prevent misoperation
3. Compatible with basket type, non-basket type and other types of dyeing racks, automatic identification, no manual conversion
4. By adjusting the flow and speed of the sealing rubber, it can be compatible with imported and domestically produced multi-standard sealing glue, stepless adjustment and real-time response.
5. Whether the dispensing needle is in real-time detection and alarm function at the working position, and a cleaning screen is designed at the storage position

SPECIFICATIONS

Model	BHTP-503
Specimen slide throughput	200-400 pieces/hour
Specimen slide holders	20-30 pieces/holder
Output magazines	30 pieces/magazine
Cover slip magazine capacity	120-160 pieces/magazine
Specimen slide size	26x75 mm
Cover slip size	24x50 mm
Net Weight	47 kg
Dimensions	590x390x620 mm
Package Info	
--Packing	Wooden Case
--Gross Weight	62 kg
--Package Dimensions	680x480x820 mm
Alt Name	Cover Slipper

FEATURES

1. Covers of various brands and specifications
2. Color touch screen control interface, real-time dynamic prompts of operation instructions, simple and efficient operation, prevent misoperation
3. Compatible with basket type, non-basket type and other types of dyeing racks, automatic identification, no manual conversion
4. By adjusting the flow and speed of the sealing rubber, it can be compatible with imported and domestically produced multi-standard sealing glue, stepless adjustment and real-time response.
5. Whether the dispensing needle is in real-time detection and alarm function at the working position, and a cleaning screen is designed at the storage position to effectively prevent the nozzle from drying (manual operation is required)
6. Automatically monitor the quality of the cover slipper during the working process. The fragments and bad pieces are automatically discarded into the waste cassette. The sensor has a self-checking function to effectively improve work efficiency.
7. Automatically carry out two rounds of slide scans during the work process, effectively reducing the leakage rate of the slides and improving the quality of work.
8. Slide grab has automatic adjustment positioning function, automatically reset after 3 failed capture and graphic and audible alarm
9. The slide out box has the function of putting it at any time and taking it at any time, and the machine automatically performs the operation; the machine without the exit box automatically detects and has the graphic sound alarm function.

10. The process of storing slides has the function of blocking automatic detection and resetting alarms.
11. Provides two modes of dry sealing and wet sealing. Users can switch between the conventional parameters as needed.
12. The alarm mode adopts various modes such as graphic display and sound, and the sound alarm automatically stops after 5 times.
13. Using large suction ultra-quiet exhaust fan, built-in replaceable activated carbon filter to enhance heat dissipation and effectively prevent air pollution



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com