



SINGLE BEAM UV VISIBLE SPECTROPHOTOMETER BHV1C7 (BSSUV-303-PC)

SINGLE BEAM UV VISIBLE SPECTROPHOTOMETER BHV1C7

SPECTROPHOTOMETER

Simple-to-use instruments with advanced performance, its stray light is only 0.05%T. The local stand-alone software provides functions of Photometry, Quantitative Test, Kinetics and System Utilities functions.



Large LCD screen (128*64 Dots).

The system can also save the test results, a total of 200 groups of data and 200 standard curves can be saved in the RAM. Convenient for check and reload.

Data can be restored after a sudden power cut.

Auto setting wavelength.

Tungsten lamp & Deuterium lamp can be turned on/off individually to extend lifetime.

The optional application software M. Wave Professional provides complete control of the spectrophotometer from a computer through the built-in USB port. It can expand to the following functions: Quantitative, Kinetics, Wavelength Scan, Multi-wavelength & DNA/Protein Test.

Pre-aligned design makes it convenient to change lamps.

SPECIFICATIONS

Model	BHV1C7
Old Model	BSSUV-303-PC
Wavelength Range	190-1100 nm
Spectral Bandwidth	4 nm
Optical System	Single Beam, Grating 1200 lines/mm
Wavelength Accuracy	±0.5 nm
Wavelength Repeatability	0.3 nm
Photometric Accuracy	±0.5%T or ±0.004A @ 1A
Photometric Range	0-200%T, -0.3-3 A, 0-9999 Conc
Stray Light	0.05%T @ 220 nm, 360 nm
Stability	±0.001 A/h @ 500 nm
Display	Graphic LCD (128*64 dots)
Keyboard	22 Membrane keypad
Standard Cell Holder	Standard 10 mm pathlength cuvette
Sample Compartment	4-position 10 mm cell changer
Light Source	Tungsten & Deuterium lamp
Output	USB Port & Parallel Port (Printer)
Power Requirement	AC 110/220 V 50/60 Hz
Dimensions (LxWxH)	470x373x187 mm
Weight	14 kg
Alt Name	Spectrophotometer

ACCESSORIES FOR PURCHASE

No	name
1	Micro Cell Holder (Beam height: 15mm)
2	8-Position Auto Cell Changer
3	4-Cell Holder for 10mm SQU.cuvette
4	4-Cell Holder for 50mm SQU.cuvette
5	4-Cell Holder for 100mm SQU.cuvette

6	Square Cuvettes Glass :10 mm
7	20 mm
8	30 mm
9	50 mm
10	100 mm
11	Square cuvettes Quartz:10 mm
12	20 mm
13	30 mm
14	50 mm
15	100 mm
16	Micro cell, Quartz (Beam height: 15mm) 100UL
17	200UL
18	500UL
19	Sipper System
20	Constant-Temperature System
21	Constant-Temperature Sipper System
22	Test Tube Holder
23	Cylindrical Cell Holder
24	Solid Sample Holder (Single Cell)
25	Water-Jacketed Cell Holder
26	10mm Water-Jacketed 4-Cell Holder
27	Milas Deuterium Lamp
28	Halogen Lamp(Philips)
29	Halogen Lamp(Philips)
30	Halogen Lamp(Osram)
31	Self Masking Cont. Flowthrough G.Cell (Beam height: 15mm) 5mm
32	10mm
33	20mm
34	30mm
35	Self Masking Cont. Flowthrough Q. Cell (Beam height: 15mm) 5mm
36	10mm
37	20mm
38	30mm
39	Thermal Printer



1



2



3



4



5



6



FEATURES

Large LCD screen (128*64 Dots).

The system can also save the test results, a total of 200 groups of data and 200 standard curves can be saved in the RAM.

Convenient for check and reload.

Data can be restored after a sudden power cut.

Auto setting wavelength.

Tungsten lamp & Deuterium lamp can be turned on/off individually to extend lifetime.

The optional application software M. Wave Professional provides complete control of the spectrophotometer from a computer through the built-in USB port. It can expand to the following functions: Quantitative, Kinetics, Wavelength Scan, Multi-wavelength & DNA/Protein Test.

Pre-aligned design makes it convenient to change lamps.

Large sample compartment; it can accommodate 5-100 mm path length cuvettes with optional holders. A variety of optional accessories are available.

Main Menu:

Move the cursor on the function menu you want, then press ENTER key to go into the corresponding interface.

☒ Basic Mode	
☐ Quantitative	
☐ Kinetics	08:00
☐ Utility	01/01

Basic Mode:

Absorbance, Transmittance or Concentration measurements.


It can display and save 200 groups of data, 5 groups per screen.

546.0nm		0.001A
No.	WL.	Abs.
1	230.0	0.001
2	340.0	0.000
3	450.0	0.002
4	540.0	0.000
5	620.0	0.003

Kinetics:


This mode may be used for time course scanning or reaction rate calculations. Abs. VS Time graphs are displayed on the screen in real time. It can record 1000 data.

Automatically records peaks and valleys.
The quantity of the curves stored is unlimited.
Post-run manipulation and processing includes:
Re-scaling axes, curve.
Smoothing, combination, zooming, overlap. 1 to 4 derivatives.



Kinetics:

The Kinetics mode may be used for scanning time courses or reacting rate calculations. Abs. Vs. Time graphs are displayed.




DNA/Protein Test:

Optional two formulas:

DNA Concentration = $62.9A_{260} - 36.0A_{280}$ or $49.1A_{260} - 75.8A_{230}$

You can also enter other wavelengths and factors to calculate.



Wavelength	Factor	Concentration
260	62.9	
280	-36.0	
260	49.1	
230	-75.8	

Functions:

Photometry

Absorbance, Transmittance or Energy measurements. It can display and save 200 groups of data, 5 groups per screen.

Quantitative

Standard Curve

At most, 9 standard samples can be used to establish a standard curve. The curve and its equation will be displayed on the screen simultaneously. You can measure your unknown concentration solutions by the curve.

A total of 200 curves can be saved in the Memory.

Coefficient Method

If the coefficient k & b in the formula $C = k \cdot a + b$ is known, you can input them directly by the button, and then test your unknown solutions.

Kinetics

This mode may be used for time course scanning or reaction rate calculations. Abs. VS Time graphs are displayed on the screen in real time. It can record 1000 data.

System Utilities

Lamp management, time & date set, obtain dark current, calibrate wavelength, default system, and some other system functions.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com