



## COOLED INCUBATOR BICL-6006

# COOLED INCUBATOR BICL-6006

## COOLING INCUBATOR

The cooling incubator has both cooling and heating functions, the lowest temperature can reach -10°C, the temperature stabilization time is short, and the temperature control precision is high. For the storage of culture media, serum, medicines, microbial culture, environmental testing, etc., it is environmental protection, sanitation and epidemic prevention, drug testing, farm animals, water Ideal thermostatic equipment for research institutes.



### Intelligent:

It provides two options: colorful touch screen controller and LCD controller. It is easy to operate. (Professional type LCD controller)

With preset power on, standby and shutdown functions.

Parameters such as multi-stage temperature, circulating wind speed, time and heating rate can be set and programmed at the same time, simplifying the complicated test process and realizing automatic control and operation.

### Specialization:

Tested and manufactured using the international DIN-12880-2007 standard.

Provide professional temperature control, high temperature control accuracy and small temperature uniformity error.

The sample can be viewed through the internal glass door without affecting the t

## SPECIFICATIONS

Model	BICL-6006
Type	Touch screen
Capacity (L)	252L
Temp Range	-10 - 80°C
Display Resolution	0.1°C
Uniformity	±1.0°C
Timing Range	1 - 5999mins
Max number of shelves	3(16)
Max load per shelf	20Kg
NW	120Kg
Interior Dimension WxDxH (mm)	550x600x750
Exterior Dimension WxDxH (mm)	695x890x1300
Electrical Requirement	AC220V/50Hz
Power Consumption	1700W
UV lamp	standard
Alt Name	Cooling Incubator

## FEATURES

### Intelligent:

It provides two options: colorful touch screen controller and LCD controller. It is easy to operate. (Professional type LCD controller)

With preset power on, standby and shutdown functions.

Parameters such as multi-stage temperature, circulating wind speed, time and heating rate can be set and programmed at the same time, simplifying the complicated test process and realizing automatic control and operation.

### Specialization:

Tested and manufactured using the international DIN-12880-2007 standard.

Provide professional temperature control, high temperature control accuracy and small temperature uniformity error.

The sample can be viewed through the internal glass door without affecting the temperature inside the box (option)

Stackable to save lab space.

Flexible shelf design for efficient use of interior space.

### Safety:

Protection of equipment: The second set of temperature limit alarm system conforms to international standards. When the heating is out of control or exceeds the maximum limit temperature, the heating is automatically cut off, and the sound and light alarm reminds the operator. Ensure that the equipment operates safely without accidents.

Protection of key components: The key electrical components are equipped with over-current, over-temperature, overload and other safety protection to prevent accidental equipment.

Protection of the sample: When the temperature inside the box is higher or lower than the set temperature, the alarm will start to cut off the heater, and the sound and light will remind the operator to protect the sample from normal test without accident.

Protection for users: The cabinet and door are specially insulated to make the surface temperature of the cabinet low, ensuring the operator's safety and no accidents.

Provide fault information: When the device fails, the display will display fault information to ensure that the fault information is clear at a glance.

### Humanized design:

With casters, flexible and convenient to move.

With reservation and timing functions, there is no need to wait, which effectively improves the efficiency of the experiment.

Available in Chinese and English menus to meet different language needs, with °C / °F conversion.

### Safety:

Protection on instruments: Comply international standard secondary temp limiting alarm system. When the heating is out of control or exceeds the maximum limit temperature, the heating is automatically cut off with sound and light alarm, ensure operating is safe without any accident.

Protection on key components: Key components are equipped with over-current, over-temperature, overload and other safety protection to prevent accident.

Protection on samples: When the temperature inside the box is higher or lower than the set temperature, the alarm will start to cut off the heater, with sound and light alarm to remind the operator to protect the sample from normal test without accident.

Protection on operator: The cabinet and door are specially insulated to make the surface temperature of the cabinet low, ensuring the operator's safety and no accidents.


Breakdown message provided: When the instrument breakdown, the message will shown on the screen to help operator clearly check.

### Convenient data processing:

The touch screen type standard with a USB interface, which can record the change status of the temperature parameters. The LCD screen is option for USB interface.


It can be equipped with RS232 data interface, which can realize remote control of the machine through software (option). RS-232 and USB can be selected as one of them.

### Precise temperature control:




The uniformity of the temperature inside the incubator chamber is  $\leq \pm 10$  degree , so that all samples are heated evenly.


Note: The stability and uniformity are the result under steady state.



Program control mode, linear temperature rise control.



Temperature fluctuation inside the incubator chamber is  $\pm 0.2$  degree, which ensures the stability of the experiment.



Program control mode, Step heating control.



Professional LCD Controller

Intelligent program control with high brightness LCD screen, button operation and real-time display of parameters. Quick setting of temperature, time and other parameters can be carried out.

It has the function of program setting. It can be programmed in 7 segments, 63 steps, 9 steps and 1-99 hours and 59 minutes per segment.



Advanced Color Intelligent Touch Screen Control

5.0 inch touch screen, intelligent touch control, real-time display of parameters, simple and convenient operation. Quick setting of temperature, time and other parameters can be carried out. It has the function of program setting.

It can be programmed in 7 segments, 63 steps, 9 steps and 1-99 hours and 59 minutes per segment.

With touch screen automatic locking function to prevent non-related personnel from disoperation.



Professional duct design:

With a unique duct design, the use of large impeller fans, fast temperature rise and fall, stable temperature control, good temperature uniformity.

The circulating fan has adjustable speed, middle and low grades, so as to avoid the volatilization of samples due to excessive air flow during the test.

Famous brand fan, high efficiency, low noise, energy saving and environmental protection.



Stainless steel inner liner:

304 stainless steel, mirror polishing, strong anti-corruption ability.

Large arc angle design, no dead angle, easy cleaning and maintenance.




**Refrigeration system:**

International brand compressors, with high refrigeration efficiency and low noise, shorten cooling time by 40% compared with traditional cryogenic equipment, save energy and protect environment.

Minimum temperature up to -10, with refrigeration and heating functions.

Automatic switching of refrigeration and heating, high control accuracy and fast temperature stability.



**Ultraviolet sterilization system (option)**

Ultraviolet lamp is located on the upper wall of the box body. It can disinfect the box body regularly and kill the plankton bacteria in the circulating air of the box body effectively so as to prevent the pollution during cell culture.



**No overturning system:**

Wire shelves with no overturning system to always operate safely.



**Reserved test hole:**

External detection sensor can real-time detect the temperature inside the box through the test hole to ensure that the temperature inside the box is accurate and reliable.



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)