



COOLED INCUBATOR BICL-7909

COOLED INCUBATOR BICL-7909

COOLING INCUBATOR



- 304 stainless steel, mirror polishing processing, easy to clean and maintain.
 - PID controller with over temperature alarm and timing function ensures precise and reliable control, also guarantee an excellent control by microprocessor and the limited number of setting keys ensures an extremely simple and intuitive operability.
 - The inner lamp for observation of the samples is standard supplied.
 - 3 fan speed meets all requirements of different experiments.
 - Famous brand compressor with refrigerant R134a.
- Option:
- Independent over-temperature alarm system ensures experiments running safely.
 - RS 485 connector can connect computer to save the data via software.
 - A side through-hole diameter of 25 mm in order to install one or more temperat

SPECIFICATIONS

Model	BICL-7909
Temperature Range	0~60°C
Display Resolution	0.1°C
Temperature Stability	Low Temperature $\pm 1.0^\circ\text{C}$
Temperature Uniformity	$\pm 2.5^\circ\text{C}$ (@25°C)
Electrical Requirement	220V 50Hz
Ambient Temperature	+5°C ~30°C
Power Consumption	2150W
Chamber Volume	1000L
Interior Dimension (WxDxH)mm	1050x590x1650
External Dimension (WxDxH)mm	1665x890x2005
Shelves	3(pcs)
Timing Range	0~5999min
Remark	standard with two doors
Packing Dimension	181*106*224
CBM	4.30
Net Weight	420.00
Gross weight	554
Alt Name	Cooling Incubator

ACCESSORIES FOR PURCHASE

No	Name
1	• Printer
2	• Intelligent programmable temperature controller
3	• $\Phi 25\text{mm}$ testing hole
4	• BOD socket
5	• RS485 connector
6	• Independent temperature-limiting Alarm



4



5

FEATURES

- 304 stainless steel, mirror polishing processing, easy to clean and maintain.
- PID controller with over temperature alarm and timing function ensures precise and reliable control, also guarantee an excellent control by microprocessor and the limited number of setting keys ensures an extremely simple and intuitive operability.
- The inner lamp for observation of the samples is standard supplied.
- 3 fan speed meets all requirements of different experiments.
- Famous brand compressor with refrigerant R134a.

Option:

- Independent over-temperature alarm system ensures experiments running safely.
- RS 485 connector can connect computer to save the data via software.
- A side through-hole diameter of 25 mm in order to install one or more temperature sensors inside the chamber.

APPLICATIONS

LED/LCD Microprocessor Controller (with timing function)

The cooling incubator is ideal for every application in microbiological field.

The range of temperature allows the growth of microorganisms in every environmental situation



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com