



COOLED INCUBATOR BICL-8002

COOLED INCUBATOR BICL-8002

COOLING INCUBATOR



LCD Programmable controller (with timing function)

- Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
- Latest PID LCD Programmable controller: 7 periods 63 steps, 0 to 5999mins for each periods, fan speed 0 to 100% adjustable.
- Independent temperature-limiting alarm system ensures experiments run safely.
- There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement.
- Using environmentally friendly R134a refrigerant, fast cooling speed, saving ene

SPECIFICATIONS

Model	BICL-8002
Controller	LCD Programmable controller
Temperature Range	-5~70°C
Display Resolution	0.1°C
Temperature Stability	High Temperature $\pm 0.3^{\circ}\text{C}$
Temperature Uniformity	$\pm 1.5^{\circ}\text{C}$ (at 25°C)
Electrical Requirement	220V 50Hz
Ambient Temperature	+5~35°C
Power Consumption	850W
Chamber Volume	150L
Interior Dimension (WxDxH)mm	500x460x800
Shelves	3(pcs)
Timing Range	0~5999min
Packing Dimension	76*75*159
CBM	0.91
Net Weight	100.00
Gross weight	141
Alt Name	Cooling Incubator

ACCESSORIES FOR PURCHASE

No	Name
1	• Printer
2	• USB data collect
3	• BOD socket
4	• UV Sterilizer
5	• RS485 connector
6	• Independent temperature-limiting Alarm



2



3



4



5

FEATURES

LCD Programmable controller (with timing function)

- Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
- Latest PID LCD Programmable controller: 7 periods 63 steps, 0 to 5999mins for each periods, fan speed 0 to 100% adjustable.
- Independent temperature-limiting alarm system ensures experiments run safely.
- There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement.
- Using environmentally friendly R134a refrigerant, fast cooling speed, saving energy and protecting environment. Auto-controller of fan speed to prevent damage to the samples.
- Shaker can be put inside BEING incubator to function as shaking incubator.
- Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature. (Option)



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com