



## COOLED INCUBATOR BICL-8004

# COOLED INCUBATOR BICL-8004

COOLING INCUBATOR



LCD Programmable controller (with timing function)

- Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
- Latest PID LCD Programmable controller: 7 periods 63 steps, 0 to 5999mins for each periods, fan speed 0 to 100% adjustable.
- Independent temperature-limiting alarm system ensures experiments run safely.
- There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement.
- Using environmentally friendly R134a refrigerant, fast cooling speed, saving ene

## SPECIFICATIONS

Model	BICL-8004
Controller	LCD Programmable controller
Temperature Range	-5~70°C
Display Resolution	0.1°C
Temperature Stability	Low Temperature $\pm 0.5^{\circ}\text{C}$
Temperature Uniformity	$\pm 1.5^{\circ}\text{C}$ (at 25°C)
Electrical Requirement	220V 50Hz
Ambient Temperature	+5~35°C
Power Consumption	2250W
Chamber Volume	495L
Interior Dimension (WxDxH)mm	670x725x1020
Shelves	3(pcs)
Timing Range	0~5999min
Packing Dimension	124*98*214
CBM	2.60
Net Weight	257.00
Gross weight	348
Alt Name	Cooling Incubator

## ACCESSORIES FOR PURCHASE

No	Name
1	• Printer
2	• USB data collect
3	• BOD socket
4	• UV Sterilizer
5	• RS485 connector
6	• Independent temperature-limiting Alarm



2



3



4



5

## FEATURES

LCD Programmable controller (with timing function)

- Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
- Latest PID LCD Programmable controller: 7 periods 63 steps, 0 to 5999mins for each periods, fan speed 0 to 100% adjustable.
- Independent temperature-limiting alarm system ensures experiments run safely.
- There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement.
- Using environmentally friendly R134a refrigerant, fast cooling speed, saving energy and protecting environment. Auto-controller of fan speed to prevent damage to the samples.
- Shaker can be put inside BEING incubator to function as shaking incubator.
- Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature. (Option)



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)