



FUNGAL GROWTH INCUBATOR BIFG-304

FUNGAL GROWTH INCUBATOR BIFG-304

FUNGAL GROWTH INCUBATOR



The shell is made of cold-rolling steel with static spray plastics, the working chamber is made of mirror stainless steel, the shelves can be adjusted optionally; PAMMA II control system, LCD screen displays temperature and time, over-temperature alarm function;
Use centrifugal fan to make the temperature of the working room uniform and stable;
Double door design, observation glass inner door;
Test holes are equipped on both sides, internal diameter is 30 mm;
Well-known international brand compressor, non-CFC refrigerant;
Equipped with mechanical lock;
Integrated type refrigeration system;

SPECIFICATIONS

Model	BIFG-304
Volume [L]	800
Type	Mould Incubator
Temp. Range Without Humidifying [°C]	0-60
Temp. Range With Humidifying [°C]	10-60
Temp. Resolution [°C]	0.1
Temp. Fluctuation at 25°C [°C]	±0.5
Temp. Uniformity at 25°C [°C]	±1
Humidity Range [%]	50-90
Humidity Fluctuation [%]	±5
Power [W]	3800
Timer Range [min/h]	0-9999
Internal Dimensions WxDxH [mm]	1220x585x1123
Housing Dimensions WxDxH [mm]	1503x910x1820
Number of Shelves [pc]	6
Net Weight/Gross Weight [kg]	298/354
Package Size [mm]	1600x1040x2020/1640x1090x2040
Alt Name	Fungal Growth Incubator

FEATURES

The shell is made of cold-rolling steel with static spray plastics, the working chamber is made of mirror stainless steel, the shelves can be adjusted optionally;
PAMMA II control system, LCD screen displays temperature and time, over-temperature alarm function;
Use centrifugal fan to make the temperature of the working room uniform and stable;
Double door design, observation glass inner door;
Test holes are equipped on both sides, internal diameter is 30 mm;
Well-known international brand compressor, non-CFC refrigerant;
Equipped with mechanical lock;
Integrated type refrigeration system;
Imported humidity sensor, electric heating humidification system, large capacity water tank;
Programmable design, it can be set 30 segments 99 cycles;
Power supply recovery function, data will not be lost when power failure and system halted.



LCD Display



Shelf



Light



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com