



GENERAL PURPOSE INCUBATOR BIGP-205

GENERAL PURPOSE INCUBATOR BIGP-205

HEATING INCUBATOR

Microprocessor Controller (with timing function)

Provided as a necessary equipment for scientific research to colleges as well as biological, agricultural and scientific research departments for storage of mould and biology cultivation.



- With inner glass door for easy observation.
 - Polished stainless-steel chamber.
 - Independent temperature-limiting alarm system ensures experiments run safely.(Option)
 - Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature.(Option)
- Options:
- Printer
 - Independent temperature-limiting Alarm system
 - RS485 connector
 - UV Sterilizer

SPECIFICATIONS

Model	BIGP-205
Electrical Requirement	220V 50Hz
Temperature Range	RT+5~65°C
Display Resolution	0.1°C
Ambient Temperature	+5~35°C
Temperature Uniformity	±1.5°C (at 37°C)
Power Consumption	600W
Chamber Volume	160L
Interior Dimension (WxDxH) mm	500x500x650
Exterior Dimension (WxDxH) mm	790x630x810
Shelves (pcs)	2
Timing Range	0-5999min
Remark	
Packing Dimension	88*72*99
CBM	0.63
Net Weight	75.00
Gross weight	95
Alt Name	Heating Incubator



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com