



GENERAL PURPOSE INCUBATOR BIGP-503

GENERAL PURPOSE INCUBATOR BIGP-503

HEATING INCUBATOR

Microprocessor Controller (with timing function)

Provided as a necessary equipment for scientific research to colleges as well as biological, agricultural and scientific research departments for storage of mould and biology cultivation.



- With inner glass door for easy observation.
- Polished stainless-steel chamber.
- Independent temperature-limiting alarm system ensures experiments run safely.(Option)
- Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature.(Option)

Options:

- Printer
- Independent temperature-limiting Alarm system
- RS485 connector
- UV Sterilizer

SPECIFICATIONS

Model	BIGP-503
Electrical Requirement	220V 50Hz
Temperature Range	RT+5~65°C
Display Resolution	0.1°C / ±0.5°C
Ambient Temperature	+5~35°C
Temperature Uniformity	±2.0 (at 37°C)
Power Consumption	2200W
Chamber Volume	1000L
Interior Dimension (WxDxH) mm	890x740x1590
Exterior Dimension (WxDxH) mm	1050x880x2060
Shelves (pcs)	4
Timing Range	0-5999min
Packing Dimension	127*95*228
CBM	2.75
Net Weight	270.00
Gross weight	377
Alt Name	Heating Incubator



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com