



GENERAL PURPOSE INCUBATOR BIGP-7701

GENERAL PURPOSE INCUBATOR BIGP-7701

HEATING INCUBATOR



LCD Programmable controller (with timing function)

- Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
- Auto-controller of fan speed to prevent damage to the samples.
- Large LCD screen to display more data at same time.
- Self-check function easy to identify problems.
- There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement.
- Programmable controller: 7 periods 63 steps, 0 ~ 5999mins for each periods, fan speed 0

SPECIFICATIONS

Model	BIGP-7701
Electrical Requirement	220V 50HZ
Controller	LCD Programmable controller
Temperature Range	RT+5°C ~80°C
Display Resolution	0.1°C
Temperature Stability	±0.2°C
Temperature Uniformity	±1.5(at 37°C)
Ambient Temperature	+5~35°C
Power Consumption	250W
Interior Dimension(WxDxH)mm	350x300x400
Exterior Dimension(WxDxH)mm	505x635x600
Shelves	2(pcs)
Timing Range	0~5999min
Remark	without observation window
Packing Dimension	81*60*76
CBM	0.37
Net Weight	44.00
Gross weight	62
Alt Name	Heating Incubator

FEATURES

LCD Programmable controller (with timing function)

- Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
- Auto-controller of fan speed to prevent damage to the samples.
- Large LCD screen to display more data at same time.
- Self-check function easy to identify problems.
- There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement.
- Programmable controller: 7 periods 63 steps, 0 ~ 5999mins for each periods, fan speed 0 to 100% adjustable.
- Independent audible and visible temperature-limiting alarm system ensures experiments run safely.

- RS485 connector can connect computer and printer to record the parameters and the variations of temperature.(Option)

Options:

- Printer
- USB data collect
- RS485 connector
- UV Sterilizer



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com