



## GENERAL PURPOSE INCUBATOR BIGP-7704

# GENERAL PURPOSE INCUBATOR BIGP-7704

## HEATING INCUBATOR



LCD Programmable controller (with timing function)

- Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
- Auto-controller of fan speed to prevent damage to the samples.
- Large LCD screen to display more data at same time.
- Self-check function easy to identify problems.
- There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement.
- Programmable controller: 7 periods 63 steps, 0 ~ 5999mins for each periods, fan speed 0

## SPECIFICATIONS

Model	BIGP-7704
Electrical Requirement	220V 50HZ
Controller	LCD Programmable controller
Temperature Range	RT+5°C ~80°C
Display Resolution	0.1°C
Temperature Stability	±0.2°C
Temperature Uniformity	±1.5(at 37°C )
Ambient Temperature	+5~35°C
Power Consumption	600W
Interior Dimension(WxDxH)mm	600x450x900
Exterior Dimension(WxDxH)mm	755x785x1130
Shelves	2(pcs)
Timing Range	0~5999min
Remark	observation window
Packing Dimension	96*86*132
CBM	1.09
Net Weight	104.00
Gross weight	150
Alt Name	Heating Incubator

## FEATURES

LCD Programmable controller (with timing function)

- Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
- Auto-controller of fan speed to prevent damage to the samples.
- Large LCD screen to display more data at same time.
- Self-check function easy to identify problems.
- There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement.
- Programmable controller: 7 periods 63 steps, 0 ~ 5999mins for each periods, fan speed 0 to 100% adjustable.
- Independent audible and visible temperature-limiting alarm system ensures experiments run safely.

- RS485 connector can connect computer and printer to record the parameters and the variations of temperature.(Option)

Options:

- Printer
- USB data collect
- RS485 connector
- UV Sterilizer



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)