



PLATELET INCUBATOR BINC-701

PLATELET INCUBATOR BINC-701

22°C PLATELET SHAKING INCUBATOR



Accurate microprocessor controller makes the inside temperature within $+22\pm 2^{\circ}\text{C}$ and resolution 0.1°C .

Suggested ambient temperature: $+10\sim 32^{\circ}\text{C}$.

Stainless steel inner chamber and shelves for friendly use and easy cleaning.

Specially designed forced-air cooling system, ensures frost-free cabinet and good temperature uniformity.

Toughened glass door with self-close function.

Wide available voltage range: $220\text{V}\pm 10\%$.

Security

Safety door lock and controller password to prevent unauthorized access.

Built-in backup battery to power the controller and save temp. data when power failure or system error.

SPECIFICATIONS

Model	BINC-701
Temperature Range	20 ~ 24°C
Ambient Temperature	10~32°C
Capacity (L / Cu. Ft.)	108 / 3.81
Interior Dimensions (WxDxH) mm	427x360x467
Exterior Dimensions (WxDxH) mm	522x600x1035
Weight	65 kgs
Noise	49 dB
Oscillation Range	50 mm
Oscillation Frequency	60 times/min
Max Loading of 450ml Blood Bag	10 Bags
Controller	Microprocessor
Display	LCD
Sensor	NTC
Voltage and Frequency	220V $\pm 10\%$, 50/60Hz
Power	197 W
Electric Current	1.3 A
Power Consumption (kWh/24h)	2.7
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 72h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Refrigeration Type	Forced-air Cooling
Defrost	Auto
Compressor (Brand/pcs)	EMBRACO / 1
Refrigerant / Weight	R134a / 53g
Door (pcs)	Self-closing Foamed Glass Door / 1
Drawer (pcs)	5
Interior Cabinet Material	Stainless Steel
Exterior Cabinet Material	Coated Steel

Insulation Material	PURF (δ45mm)
Door Lock	Yes
LED Lamp	UV Lamp
Test Hole (pcs)	Optional
Castors (pcs)	4
Temperature Printer	Yes
Remote Alarm Port	Yes
USB Data Download Port	Optional
RS485 Port	Optional
Temperature Datalogger	Optional
Package	Plywood box with pallet
Shipping Weight	87 kgs
Shipping Size (WxDxH) mm	700x590x1210
Shipping Volume	0.5 CBM
Alt Name	22°C Platelet Shaking Incubator



FEATURES

Accurate microprocessor controller makes the inside temperature within $+22\pm 2^{\circ}\text{C}$ and resolution 0.1°C .
Suggested ambient temperature: $+10\sim 32^{\circ}\text{C}$.
Stainless steel inner chamber and shelves for friendly use and easy cleaning.
Specially designed forced-air cooling system, ensures frost-free cabinet and good temperature uniformity.
Toughened glass door with self-close function.
Wide available voltage range: $220\text{V}\pm 10\%$.

Security

Safety door lock and controller password to prevent unauthorized access.
Built-in backup battery to power the controller and save temp. data when power failure or system error.
Visual and audible alarm system.
Power failure protection: turn-on delay of the cooling system after power failure.
Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

Humanized design

Special designed service-free drainage system, ensure no water in the cabinet.
4 casters with stopper for easy moving and fixation.
UV sterilization: adjustable sterilization time and auto on/off when the door is closed/opened.

APPLICATIONS

The $+22^{\circ}\text{C}$ blood platelet shaking incubators are specially designed to store platelet for hospitals and blood stations.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com