



NATURAL CONVECTION INCUBATOR BINC-7804

NATURAL CONVECTION INCUBATOR BINC-7804

NATURAL CONVECTION INCUBATOR



Technical Advantage Performance and Features

- Temperature Range: Amb+5°C ~65°C .
- P.I.D temperature controller provides accurate and reliable temperature control.
- Natural convection heating allows the sample temperature to be uniform, suitable for sterilization, powder drying and high temperature storage.
- Extended Life Silicone Rubber Gasket provides excellent sealing and long service life, but is easily replaced when the time for replacement is needed.

Convenience

- Volume(10L~210L).
- Inner chamber is made from corrosion-resistant mirror stainless steel.
- Round curved inner angle is easy to clean.

SPECIFICATIONS

Model	BINC-7804
Electrical Requirement	220V 50Hz
Temperature Range	Amb+5~65°C
Display Resolution	0.1°C
Ambient Temperature	+5~35°C
Power Consumption	550W
Inner Glass Door	Has
Viewing Window	None
Chamber Volume	115L
Interior Dimension (WxDxH ,mm)	520x450x495
Exterior Dimension (WxDxH ,mm)	785x587x715
Shelves	3PCS
Packing Dimension	90*72*96
CBM	0.62
Net Weight	65.00
Gross weight	90
Alt Name	Natural Convection Incubator

FEATURES

Technical Advantage Performance and Features

- Temperature Range: Amb+5°C ~65°C .
- P.I.D temperature controller provides accurate and reliable temperature control.
- Natural convection heating allows the sample temperature to be uniform, suitable for sterilization, powder drying and high temperature storage.
- Extended Life Silicone Rubber Gasket provides excellent sealing and long service life, but is easily replaced when the time for replacement is needed.

Convenience

- Volume(10L~210L).
- Inner chamber is made from corrosion-resistant mirror stainless steel.
- Round curved inner angle is easy to clean.
- Anti-skid shelf design, easy to operate by single hand.

Safety

- Auto Start Feature after power loss/return.
- Temperature deviation alarm.
- Over current protection alarm.
- Independent Over-temperature protection meets DIN 12880 International standard

requirements provides you double protection.(Option)

Options:

- Intelligent programmable temperature controller
- Independent temperature-limiting Alarm system
- RS485 connector



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com