



THERMAL IMAGING CAMERA METERS BJF1C1 (BMET-102)

THERMAL IMAGING CAMERA METERS BJF1C1

THERMAL IMAGING CAMERA METERS

Thermal imaging cameras are non-contact devices used to capture detailed images in low-light environments. It works by detecting infrared energy (heat) which interprets temperature as colour and converting it into an image in real-time. Red and yellow colours depicts warmer areas and purple or blue colours depict cooler areas.



SPECIFICATIONS

Model	BJF1C1
Old Model	BMET-102
Display screen	3.2" full angle TFT/display screen
Infrared image resolution	220x160
Visible image resolution	300,000 pixel
Field angle/shortest focus length	27°x35° / 0.15 m
Thermal sensitivity	0.07 °C
Temperature measurement range	-20 °C~300 °C (-4 °F~572 °F)
Measurement accuracy	±2% digital / ±2 °C
Emissivity	Adjustable from 0.01 to 1.0
Frame rate of thermal images	9 Hz
Wavelength coverage	8-14 μm
Focus mode	Fixed
Color palette	Rainbow, iron oxide red, cold color, black & white, white & black
View option	The integration of thermal image with 25% step length and visible image
Storage medium	Built-in 3G (above 20 thousand images stored)
File format	JPG
USB	Micro USB 2.0
Power supply	Built-in rechargeable 18650 battery
Automatic power-off time	Selectable: 5 min / 20 min / not power off automatically
Product size (LxWxH)	90x105x223 mm
Product weight	389 g
Work temperature	0 °C to 45 °C
Storage temperature	-20 °C to 60 °C
Relative humidity	<85% RH
Alt Name	Thermal Imaging Camera Meters



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com