



PORTABLE SPECTROCOLORIMETER BJH1E2 (BPSP-1102)

PORTABLE SPECTROCOLORIMETER BJH1E2

SPECTROCOLORIMETER FOR ACCURATE MEASUREMENT

The Portable Spectrocolorimeter is a compact, handheld color measurement device designed to provide stable color comparisons for materials and products wherever color control is important. Its rugged, ergonomic design ensures portability and durability for field inspections or production lines, providing efficient, reliable color measurement solutions for demanding environments.



CMOS dualbeam splitting sensor
CIE LAB, XYZ, LCH, and sRGB color spaces
D/8° optical geometry (SCI/SCE)
Two measurement apertures (φ8mm and φ4mm)
400 700 nm full waveband balanced LED light source
3.5inch TFT touchscreen offers an intuitive user interface
Excellent repeatability ($\Delta E_{ab} \leq 0.08$) and interinstrument agreement ($\Delta E_{ab} \leq 0.25$)
Adopt full waveband balanced LED light source
Silicon photodiode array sensor (32 groups with double rows)
A variety of color space, a variety of observation light sources
Interface instruction
Adopt international common use d/8 SCI/SCE Synthesis technology

SPECIFICATIONS

Model	BJH1E2
Old Model	BPSP-1102
Optical Geometry	D/8°
Standards compliant	CIE No.15, GB/T 3978, GB 2893, GB/T 18833, ISO77241, ASTM E1164, DIN5033 Teil7
Integrating Sphere Size	Φ40 mm
Light Source Device	Combined LED Lamp
Spectroscopic Method	Flat grating
Sensor	Silicon photodiode array (double row 32 groups)
Light wave range	400-700 nm
Wavelength Pitch	10 nm
Semiband Width	10 nm
Measured Reflectance Range	L: 0-120; reflectivity: 0-200%
Measuring Aperture	Single apertures - φ8 mm/φ10 mm
Specular Component	SCI/SCE
Color Space	CIE LAB, XYZ, Yxy, LCh, sRGB, βxy, Munsell (C/2)
Color Difference Formula	ΔE^*_{ab} , ΔE^*_{94} , $\Delta E^*_{cmc}(2:1)$, $\Delta E^*_{cmc}(1:1)$, ΔE^*_{00} , DINΔE99
Other Colorimetric Index	WI (ASTM E313, CIE/ISO, AATCC, Hunter), YI (ASTM D1925, ASTM 313), Metamerism Index MI, Staining Fastness, Color Fastness, Color Strength, Opacity, Color Card Search
Observer Angle	2°/10°
Illuminant	D65, A, C, D50, F2 (CWF), F7 (DLF), F10 (TPL5), F11 (TL84), F12 (TL83/U30)
Displayed Data	Spectrogram/Values, Samples Chromaticity Values, Color Difference Values/Graph, PASS/FAIL Result, Color Simulation, Color Offset
Displayed Accuracy	0.01
Measuring Time	About 1.5 s (Measure SCI & SCE about 3.2 s)
Repeatability	Chromaticity value: MAV/SCI, within ΔE^*_{ab} 0.06 (When a white calibration plate is measured 30times at 5 second intervals after white calibration)
Interinstrument Error	MAV/SCI, Within ΔE^*_{ab} 0.3 (Average for 12 BCRA Series II color tiles)
Measurement Mode	Single Measurement, Average Measurement (2-99 times)
Locating Method	Camera Locating, stabilizer cross position

Dimension	LxWxH = 81 x 71 x 214 mm
Weight	About 460 g
Battery	Li-ion battery; 6000 measurements within 8 hours
Illuminant Life Span	5 years; more than 3 million times measurements
Display	3.5-inch TFT color LCD; Capacitive Touch Screen
Data Port	USB
Data Storage	Standard 1000 Pcs; Sample 20,000 Pcs (one data can include SCI/SCE)
Language	Simplified Chinese, English, Traditional Chinese
Operating Environment	0-40 °C, 0-85% RH (no condensing); Altitude < 2000 m
Storage Environment	-20-50 °C, 0-85% RH (no condensing)
Standard Accessory	Power Adapter, USB Cable, User Guide, PC Software (download from office website), White & Black Calibration Cavity, Protective Cover, Wrist strap, 8 mm flat aperture, 8 mm tip aperture, 4 mm flat aperture, 4 mm tip aperture
Optional Accessory	USB Micro Printer, Powder Test Box, Bluetooth Micro Printer
Alt Name	SpectroColorimeter




FEATURES

CMOS dualbeam splitting sensor
 CIE LAB, XYZ, LCH, and sRGB color spaces
 D/8 optical geometry (SCI/SCE)
 Two measurement apertures ($\phi 8\text{mm}$ and $\phi 4\text{mm}$)
 400 700 nm full waveband balanced LED light source
 3.5inch TFT touchscreen offers an intuitive user interface
 Excellent repeatability ($\Delta E_{ab} \leq 0.08$) and interinstrument agreement ($\Delta E_{ab} \leq 0.25$)
 Adopt full waveband balanced LED light source
 Silicon photodiode array sensor (32 groups with double rows)
 A variety of color space, a variety of observation light sources



Interface instruction




Adopt international common use d/8 SCI/SCE Synthesis technology
 Spectrocolorimeter adopts D/8(diffused illumination, 8degree viewing angle) which is widely applicable in the world, and SCI/SCE

(specular component included/specular component excluded) Synthesis technology. It is suitable for color management and quality control in various industries such as color matching and coating, textile, plastic, food, building materials, cosmetics, etc.



Ergonomic design and easy measuring device :

The spectrophotometer has a beautiful, smooth shape and comfortable grip, in line with the structure design of human mechanics, fit the palm for continuous testing, so that you can use it quickly and easily. An automatic measuring device is added, which is portable, quick and easy to measure.



Standard whiteboard


ETC realtime calibration technology:

The spectrophotometer adopts imported standard white board, which is resistant to yellowing and dirt infiltration and can be wiped, ensuring the long-term accuracy of the instrument. An innovative ETC realtime calibration technique is also used, with a builtin standard white board into the optical system, which is reliably accurate and repeatable for each Test.



Camera locating can clearly observe the measured area:

A spectrophotometer has a builtin camera for positioning, which can accurately determine whether the measured part of the object is the center of the target through realtime viewing by the camera, thus improving the measurement efficiency and accuracy.



Color management software:

SQCX quality management software with spectrophotometer is suitable for quality monitoring and color data management in various industries. Data the user's color management, compare color differences, generate test reports, provide multiple color space measurement data, and customize the customer's color management.

APPLICATIONS

With 8mm and 4mm dual apertures, spectrophotometer is widely suitable for the industry production and quality inspection of accurate color difference control like plastic electronics, paint and ink, textile printing and dyeing, printing, ceramic industry etc.



Building materials



Coatings



Textile



Plastics



Food



Cosmetics



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com