



TESTER PETROLEUM EQUIPMENT B JL1BM1

TESTER PETROLEUM EQUIPMENT BJL1BM1

OXIDATION STABILITY TESTER



The glass test tube meets the requirements of ASTM standards;
Electronic timer, digital display, with alarming;
Precision flow meter regulates gas flow, separate flow control;
Six test tubes can work at the same time, with fan cooling;
Three-dimensional Structure;
Stainless steel heater, heating bath;
Imported Omron PID temperature controller, digital display temperature, accuracy 0.1 °C

SPECIFICATIONS

Model	BJL1BM1
Applicable standards	ASTM D2274, ISO12205, SH/T0175
Temperature control method	Digital PID temperature controller
Circulating method	Magnetic pump circulation
Temperature control range	20-95°C ±0.2°C
Working units	6 tubes
Flow tube control	Adjusted by flow meter
Timing method	Electronic timing, automatic alarming
Power supply	220V, 50Hz
Power consumption	2500W
Dimension	63*71*93 cm
Weight	50KG
Alt Name	Oxidation Stability Tester


ITEMS INCLUDED

No	Name	Quantity
1	Main unit	1 Set
2	Oxidation tube	6 PCS
3	Glass condenser	6 PCS
4	Silicon tube φ6	5 Meter
5	Fuse 20A	4 PCS
6	Oxygen pipe	6 PCS
7	Buffer tank	2 PCS
8	Manual book	1 Copy

FEATURES

The glass test tube meets the requirements of ASTM standards;
Electronic timer, digital display, with alarming;
Precision flow meter regulates gas flow, separate flow control;
Six test tubes can work at the same time, with fan cooling;
Three-dimensional Structure;
Stainless steel heater, heating bath;

Imported Omron PID temperature controller, digital display temperature, accuracy 0.1 °C



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com