



METERS PETROLEUM EQUIPMENT BJO1BV1 (BPTL-305)

METERS PETROLEUM EQUIPMENT BJO1BV1

AUTOMATIC OXYGEN BOMB CALORIMETER

Meters of Petroleum Equipment measure the consistency of lubricating greases (Penetrometer) or determining their heat value which do not contain water, coal, paraffin and other combustible substance (Oxygen Bomb Calorimeter) or can trace low levels of free, emulsified and dissolved (Coulometric Karl Fischer Titrator)



Adopting semiconductor refrigeration to decide the refrigerating capacity according to the calorific value, the instrument can automatically adjust water temperature and keep water in a relative constant temperature range, realize the continuously and long time test requirement, and make sure the test result is correct. Using USB port, convenient to connect. One computer can control many sets of Oxygen Bomb Calorimeter. Adopting professional discharge water ports, more convenient and fast when the instrument drains away water or change the water. The electronic balance with communication function to share the data by the internet.

SPECIFICATIONS

Model	BJO1BV1
Old Model	BPTL-305
Pressure endurance of oxygen bomb	20 MPa
Measuring temperature range	5°C ~ 40°C
Temperature resolution	0.0001°C
RSD (Relative standard deviation)	≤0.1%
Test time period: main period	about 8 mins
Measuring range	5MJ/kg ~ 40MJ/kg
Measuring error	±60 J/g (Benzoic acid)
Accuracy	Better than GB/T213-2008 "The determination method of coal calorific value"
Ambient temperature	15°C ~ 35°C
Relative humidity	≤ 85%
Dimension	650x450x450 mm
Net weight	55 kg
Alt Name	Automatic Oxygen Bomb Calorimeter

APPLICATIONS

Petroleum Industry, Petrochemical Industry, Oil Industry



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com