PRODUCT CATALOG

CLASS B AUTOCLAVE BJT-701

CE ISO9001 CERTIFIED

www.biolabscientific.com

CLASS B AUTOCLAVE BJT-701

TABLE TOP STEAM STERILIZER (CLASS B)

LCD Display.
Electronic Safety Door Interlock.
High-quality Stainless Steel Chamber, Sealed Cover.
Microcomputer Control, Fully Automated Process Control.
Automatic Fault Detection.
High Altitude Adaptive System, Automatic Atmospheric Pressure Calibration.
9 Preset Programs, 3 Test Programs.
Equipped with Standard Test Interface.
European Class B Standard, Triple Pulsed Vacuum.
Comprehensive Automatic Protection Functions for the Machine.
Built-in High-efficiency Independent Steam Generator, Quickly and Stably Provides Saturated Steam.

SPECIFICATIONS

Model	BJT-701
Capacity	8L
Sterilization Temperature	134°C
Working Pressure	0.22 MPa
Features	
Power	2.2KW
Voltage	AC 110V 60HZ or AC 220V 50HZ
Design pressure	-0.1~0.25MPa
Design temperature	139°C
Sterilization temperature range	116~134°C
Sterilization time range	4~ 120 min
Drying time range	0~240 min
Chamber Size(mm)	Φ170x320
Overall dimensions (mm)	445x580x400
Packing dimensions (LxWxH)(mm)	640x500x450
Gross weight/Net weight	49/40kg
Alt Name	Table Top Steam Sterilizer(Class B)

FEATURES

LCD Display.
Electronic Safety Door Interlock.
High-quality Stainless Steel Chamber, Sealed Cover.
Microcomputer Control, Fully Automated Process Control.
Automatic Fault Detection.
High Altitude Adaptive System, Automatic Atmospheric Pressure Calibration.
9 Preset Programs, 3 Test Programs.
Equipped with Standard Test Interface.
European Class B Standard, Triple Pulsed Vacuum.
Comprehensive Automatic Protection Functions for the Machine.
Built-in High-efficiency Independent Steam Generator, Quickly and Stably Provides Saturated Steam.
Built-in Printer, USB Function.
Optional Water Quality Testing Function.

Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com