



CLASS III BIOSAFETY CABINET BJU-102

CLASS III BIOSAFETY CABINET BJU-102

BIOLOGICAL SAFETY CABINET



Advantage:

Memory function in case of power-failure.

UV sterilization with UV lamp timing function.

Work area surrounded by negative pressure, prevent leakage, improve biosafety.

Audio and Visual alarm, including abnormal pressure and filter replacement.

With double exhaust ULPA filters, >99.9995% efficiency at 0.12 μm.

Ergonomic 10° tilt Angle improves the operation comfort.

Airflow Pattern:

LCD Display:

Large display is easy to monitor the pressure parameters for work zone and three filters.

Pressure Meter:

SPECIFICATIONS

Model	BJU-102
External Size (WxDxH)	1790x880x2080 mm
Internal Size (WxDxH)	1165x680x680 mm
Pass Box External Size (WxDxH)	-
Pass Box Internal Size (WxDxH)	-
Control System Display	LCD display
Control System Alarm	Audio and Visual alarm, including abnormal pressure and filter replacement
--Pre-Filter	Polyester fiber, washable (Negative pressure ≥ 120 Pa)
--ULPA Filter	Air supply filter First exhaust filter Second exhaust filter
--Cleanliness Grade	Class 100 (ISO14644.1 Class 5)
Cabinet Construction	
--Main Body	Electro-galvanized steel with antimicrobial Powder Coating
--Work Surface	304 stainless steel
--Front Window	8mm toughened glass, anti-ultraviolet radiation
--Gloves	One pair of 800mm butyl rubber gloves
Electrical System	
--UV Lamp	30Wx2, 8Wx1
--LED Lamp	16Wx2
--Max. Consumption	1300W
--Power Supply	AC220V $\pm 10\%$, 50/60Hz; 110V $\pm 10\%$, 60Hz
Illumination	≥ 1000 Lux
Sound Emission	≤ 70 dB(A)
Standard Accessory	1.Glovesx1 pair; 2.LED Lampx2; 3.UV Lampx3; 4.Pressure Meter; 5.Drain Valve; 6.ULPA Filters; 7.Footmaster Caster; 8.Waterproof Socketx2
Gross Weight	450 kg
Shipping Size (WxDxH)	1800x1065x2250 mm
Shipping Volume	4.5 m ³
Alt Name	Biological Safety Cabinet

FEATURES

Advantage:

Memory function in case of power-failure.

UV sterilization with UV lamp timing function.


Work area surrounded by negative pressure, prevent leakage, improve biosafety.

Audio and Visual alarm, including abnormal pressure and filter replacement.

With double exhaust ULPA filters, $\geq 99.9995\%$ efficiency at $0.12 \mu\text{m}$.

Ergonomic 10° tilt angle improves the operation comfort.

Airflow Pattern:



LCD Display:

Large display is easy to monitor the pressure parameters for work zone and three filters.




Pressure Meter:

Display the pressure of the work zone.



Butyl Rubber Gloves:

Strong wear resistance and corrosion resistance



UV Lamp:

Emission of 253.7 nanometers for most efficient decontamination



Pass Box:
Double doors with interlock function and UV lamp.



Waterproof Socket (IP54)



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com