



-150°C CRYOGENIC FREEZER BZX-102

-150°C CRYOGENIC FREEZER BJX-102

-150°C CRYO FREEZER



Temperature Control System

Microprocessor control, Large touch screen inner temperature clearly, and with easy viewing.

The inner temperature can be adjustable at the range of -125°C~-150°C.

Lock and password for protection to prevent arbitrary adjustment of operating parameters.

Safety protection measures

Malfunction alarms: high temperature alarm, low temperature alarm, Sensor failure.


Three alarming methods: buzzer alarming, digital flashing alarming and remote contacts.

Protection function: power-on delay, time between stops.

SPECIFICATIONS

Model	BJX-102
Capacity	226L
Temperature range	-125~-150°C
Cabinet Type	Chest
Climate Class	N
Cooling Type	Direct Cooling
Defrost Mode	Manual
Refrigerant	CFC Free
Temperature Setting (°C)	-150
Controller	Microprocessor
Display	7"-inch touchscreen with USB port
Exterior Material	Galvanized steel powder coating
Interior Material	Stainless steel
Rated Voltage (V/Hz)	220/50
Power (W)	2000
Current (A)	11
High/Low Temperature Alarm	Yes
Sensor Error Alarm	Yes
Lockage	Yes
Foot	Yes
Baskets/Inner Doors	2 / -
Racks & Boxes	Optional
Net/Gross Weight (approx.)	230/280 kg
Interior Dimensions (WxDxH)	780x580x500 mm
Exterior Dimensions (WxDxH)	1510x940x1000 mm
Package Dimensions (WxDxH)	1570x980x1150 mm
Container Loading (20'/40')	12/28
Capacity for 2-inch Boxes	160
Alt Name	-150°C Cryo Freezer

ACCESSORIES FOR PURCHASE

No	Image	Name
1		Cryo Racks
2		Cryo Boxes
3		Co2/LN backup device
4		Chart temperature recorder
5		Wireless Monitoring system

FEATURES

Temperature Control System

Microprocessor control, Large touch screen inner temperature clearly, and with easy viewing.

The inner temperature can be adjustable at the range of -125°C~-150°C.

Lock and password for protection to prevent arbitrary adjustment of operating parameters.

Safety protection measures

Malfunction alarms: high temperature alarm, low temperature alarm, Sensor failure.

Three alarming methods: buzzer alarming, digital flashing alarming and remote contacts.

Protection function: power-on delay, time between stops.

Refrigeration System

Optimized cascade refrigeration technology, SECOP compressor to reach a high efficient refrigeration effect.
Specially designed Heat Exchanger, heat transfer high efficient, save energy.
Independent engine cabinet cooling system, ensure to adapt to a higher ambient temperatures.
CFC-Free overall situ polyurethane foaming insulation.
CFC-Free refrigerant.

Ergonomic Design

Safety door lock, preventing unauthorized access.
Wide voltage design from 192V to 242V.
Stainless steel inner chamber, easy for clean.
Heavy type caster and locking adjustable screw,easy to move and fix.

APPLICATIONS

-150°C Cryo Freezer provides a safer, more convenient and economical alternative long term storage method than LN2 containers. We design it to provide a storage environment that is 3 about 20°C colder than the water recrystallization temperature. The freezer is suitable for storage of a variety of biological samples, such as virus, erythrocytes, leukocytes, cutis, skeleton, sperm, oceanic products, special test materials and even electronic products for testing. It can be installed in institutions including blood banks, hospitals, epidemic prevention service centers, research institutes and laboratories.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com