



4°C BLOOD BANK REFRIGERATOR BJX-1104

4°C BLOOD BANK REFRIGERATOR BJX-1104

4°C BLOOD BANK REFRIGERATOR



Temperature Control

Microprocessor control, Large LED display inner temperature clearly, and with easy viewing.

The inner temperature can be adjustable at the range of 2°C~6°C, with an increment of 0.1°C.

Multiple sensors to display or control the temperature.

Lock and password for protection to prevent arbitrary adjustment of operating parameters.

Safety Control

Malfunction alarms: high temperature alarm, low temperature alarm, Sensor failure, Power failure alarm, low voltage of backup battery, Over temperature alarm system, set the

SPECIFICATIONS

Model	BJX-1104
Capacity	1073L
Temperature range	2~6°C
Defrost Mode	Auto
Climate Class	N
Cooling Type	Forced air cooling
Cabinet Type	Upright
Refrigerant	R290
Cooling performance(°C)	4
Power Supply(V/Hz)	220/50
Power(W)	400
Power Consumption	4.6
Controller	Microprocessor
Display	LED
Temperature control/display accuracy	0.1
Temperature sensors	4
Anti-low temperature control device	Mechanical
The minimum temperature of Mechanical control	2
Interior	Stainless steel
Exterior	Galvanized steel powder coating(white)
Net/Gross Weight(approx)	220kg/252kg
Interior Dimensions(W*D*H)	1180x690x1400mm
Exterior Dimensions(W*D*H)	1300x830x1965mm
Package Dimensions(W*D*H)	1340x880x2175mm
Interior high/low temperature alarm	Yes
Power failure alarm	Yes
Sensor failure alarm	Yes
Door open alarm	Yes
Door lock	Yes
Inner LED light	Yes
Data storage (sets)	100,000+

Temperature Recorder	Yes
Remote alarm contact	Yes
Castor/Foot	-/4
Test Hole	Yes
7 days Chart temperature recorder	Optional
Shelves/Inner Doors	5/-
Drawer	Optional (12)
Alt Name	4°C Blood Bank Refrigerator

FEATURES

Temperature Control

Microprocessor control, Large LED display inner temperature clearly, and with easy viewing.

The inner temperature can be adjustable at the range of 2°C~6°C, with an increment of 0.1°C.

Multiple sensors to display or control the temperature.

Lock and password for protection to prevent arbitrary adjustment of operating parameters.

Safety Control

Malfunction alarms: high temperature alarm, low temperature alarm, Sensor failure, Power failure alarm, low voltage of backup battery, Over temperature alarm system, set the alarm temperature as requirements.

Three alarming methods: buzzer alarming, digital flashing alarming and Remote alarm.

Protection function: power-on delay, time between stops.

Chart temperature recorder-monitor system (Optional).

Refrigeration System

Highly efficient famous brand compressor and fan, with a high efficient refrigeration effect.

70mm thick foam insulation, better insulation effect, help to maintain temperature stability inside the refrigerator.

Forced-Air Circulation for large airflow with special air ducts to guarantee inner temperature consistency.

Monoblock refrigeration units, energy-efficient and easy for maintenance.

CFC-Free/HCFC refrigerant.

Ergonomic Design

Safety door lock, preventing unauthorized access.

Auto defrost function guarantees a good performance in high ambient temperature and humidity area.

Wide voltage design from 192V to 242V.

Inner LED lighting and caster design.

No condensation glass door.

USB export interface for event and temperature data .

Baskets or stainless steel drawers (Optional).

APPLICATIONS

Auto Defrost, Forced-Air Circulation Suitable for hospitals, blood banks, epidemic prevention, animal husbandry areas, pharmaceutical companies and research institutes.

Designed to store blood, medicine.

Microprocessor control, Large LED display inner temperature clearly, and with easy viewing.

The inner temperature can be adjustable at the range of 2°C~6°C, with an increment of 0.1°C.

Multiple sensors to display or control the temperature.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com