



BENCHTOP HIGH SPEED REFRIGERATED CENTRIFUGE BKA-801

HIGH SPEED REFRIGERATED CENTRIFUGE BKA-801

BENCHTOP HIGH SPEED REFRIGERATED CENTRIFUGE



1. Microprocessor control with AC Brushless Motor
2. CFC free cooling system with pre-cooling function.
3. 5 Inches Colorful LCD Display the parameters of speed, timer, RCF, Temperature, rotors information, Program (Memory) information, Acceleration & Deceleration information and Error code information.
4. Steel centrifuge body and 304# stainless steel chamber are autoclaveable and resistant detergents and disinfection liquids.
5. Gas hinge for lid drop protection.
6. Safety Electrical lid interlock, door can not open when rotor is running and machine won't run when lid open and error code appears.
7. Emergency lid lock release when power failure.
8. Window on lid for speed calibration and noise measurement.

SPECIFICATIONS

Model	BKA-801
Max. Speed	20000rpm
Max. RCF	27800xg
Max. Capacity	4x100ml
Noise(dBA)	≤58dB(A)
Time range	1-99minutes
Temperature range(°C)	-20°C~+40
Speed accuracy	±20r/min
Temperature accuracy	±2°C
Dimension(mm)(W*D*H)	620*500*350mm
Net weight(without rotor)	60KGS
Power supply	AC220-240V,50/60HZ,10A,0.8KW
Alt Name	Benchtop High Speed Refrigerated Centrifuge

ACCESSORIES FOR PURCHASE

No	name	Capacity (ml)	Max. Speed(rpm)	Max. RCF (xg)
1	NO.1 Fixed rotor	Adapter:12x0.2ml	20000rpm	20380xg
2	NO.2 Fixed rotor	Adapter:12x0.2ml	20000rpm	27800xg
3	NO.3 Fixed rotor	Adapter:24x0.2ml	16000rpm	23800xg
4	NO.4 Fixed rotor	Adapter:48x0.2ml	16000rpm	21900xg
5	NO.5 Fixed rotor	Adapter:10x0.2ml Adapter:10x0.5ml Adapter:10x1.5/2.2ml	16000rpm	17780xg
6	NO.6 Fixed rotor	Adapter:12x0.2ml Adapter:12x0.5ml Adapter:12x1.5/2.2ml	15000rpm	19910xg
7	NO.7 Fixed rotor	Adapter:6x0.2ml Adapter:6x0.5ml Adapter:6x1.5/2.2ml Adapter:6x5ml Adapter:6x10ml Adapter:6x15ml Adapter:6x20ml Adapter:6x30ml All can be custom made	13000rpm	18550xg
8	NO.8 Fixed rotor	Adapter:4x0.2ml Adapter:4x0.5ml Adapter:4x1.5/2.2ml Adapter:4x5ml Adapter:4x10ml Adapter:4x15ml Adapter:4x20ml Adapter:4x30ml Adapter:4x50ml	11000rpm	13280xg
9	NO.9 Fixed rotor	Adapter:48x0.2ml	13000rpm	17980xg

10	NO.10 Swing rotor	2x2x48 micro plate	4000rpm	1505xg
11	NO.11 Fixed rotor	18*5ml	17000rpm	24280xg
12	NO.12 Fixed rotor	18*5ml	13000rpm	15800xg

FEATURES

1. Microprocessor control with AC Brushless Motor
2. CFC free cooling system with pre-cooling function.
3. 5 Inches Colorful LCD Display the parameters of speed, timer, RCF, Temperature, rotors information, Program(Memory) information, Acceleration & Deceleration information and Error code information.
4. Steel centrifuge body and 304# stainless steel chamber are autoclaveable and resistant detergents and disinfection liquids.
5. Gas hinge for lid drop protection.
6. Safety Electrical lid interlock, door can not open when rotor is running and machine won't run when lid open and error code appears.
7. Emergency lid lock release when power failure.
8. Window on lid for speed calibration and noise measurement.
9. Continuous operation, working continuous according the set time.
10. 10 kinds of Program(Memory) and 10 kinds of Acceleration & Deceleration for choice. If ask for more Programs please specially mentioned when place the order.
11. Automatic troubleshooting with indication of error code and alarm on the screen.
12. Wide choice of rotors are autoclaveable.
13. With CE and ISO9001:2008, ISO13485 certificate.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com