



-50°C CHEST FREEZER BKD-104

-40°C FREEZER BKD-104

-50°C LOW TEMPERATURE CHEST FREEZER



SPECIFICATIONS

Model	BKD-104
Capacity	480L
Temperature Range	-15°C ~ -50°C
Climate class	T
Unit dimensions	1990*960*975 mm
Interior dimensions	1300*600*600 mm
Power supply	220V/50Hz or 115V/60Hz
Rated input	400 W
Power consumption	5.60 kW.h/24h (FRO)
Refrigerants	Mixed CFC free refrigerants
Compressor	World brand compressor
Temp. controller	Brand electronic controller
Temperature display	Digital temperature display
Evaporator	Wall type copper tube evaporator
Condenser	AI finned copper tube condenser
Condensation fan	German brand, EBM fan
Insulation thickness	130 mm
Material of interior	SUS 304
Door	Foamed door, top open
Door handle	Recessed door handle with lock
Baskets	NA
Casters	4 pcs, casters
Net weight	190 kg
Alt Name	-50°C low temperature chest freezer

APPLICATIONS

-50°C low temperature chest freezers are used in the fields of biological study, bio-pharmacy, low temperature tests and fresh storage of foods. The freezers can be used for freezing storage of biological samples and products and bio-chemical reagents; low temperature tests and treatment of chemical, electronic and metal materials and parts; low temperature storage of deep sea foods and high grade foods.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com