



-50°C UPRIGHT FREEZER BKD-204

-40°C FREEZER BKD-204

-50°C LOW TEMPERATURE UPRIGHT FREEZER



SPECIFICATIONS

Model	BKD-204
Capacity	105L
Temperature Range	-15°C ~ -50°C
Climate class	T
Unit dimensions	775*740*1275 mm
Interior dimensions	455*460*500 mm
Power supply	220V/50Hz or 115V/60Hz
Rated input	170W
Power consumption	2.00 kW.h/24h (FRO)
Refrigerants	Mixed CFC free refrigerants
Compressor	World brand compressor
Temperature controller	Brand electronic controller
Temperature display	Digital temperature display
Evaporator	Wall type copper tube evaporator
Condenser	Al finned copper tube condenser
Condensation fan	German brand, EBM fan
Insulation thickness	120 mm
Material of interior	SUS 304
Shelf	One pcs, stainless steel
Door handle	OX-Head handle with lock
Inner door	2 pcs, SUS304 stainless steel
Casters	4 pcs, casters
Net weight	90 kg
Alt Name	-50°C Low Temperature Upright Freezer

APPLICATIONS

-50°C low temperature upright freezers are used in the fields of biological study, bio-pharmacy, low temperature tests and fresh storage of foods. The freezers can be used for freezing storage of biological samples and products and bio-chemical reagents; low temperature tests and treatment of chemical, electronic and metal materials and parts; low temperature storage of deep sea foods and high grade foods.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com