



-50°C CHEST FREEZER BKD-302

-40°C FREEZER BKD-302

-50°C LOW TEMPERATURE CHEST FREEZER



SPECIFICATIONS

Model	BKD-302
Capacity	50L
Temperature Range	-15°C ~ -50°C
Climate class	T
Unit dimensions	672*630*785 mm
Interior dimensions	465*350*285 mm
Power supply	220V/50Hz or 115V/60Hz
Rated input	130 W
Power consumption	1.52 kW.h/24h (FRO)
Refrigerants	Mixed CFC free refrigerants
Compressor	World Brand compressor
Temperature controller	Brand electronic controller
Temperature display	Digital temperature display
Evaporator	Wall type copper tube evaporator
Condenser	Al finned copper tube condenser
Condensation fan	German brand, EBM fan
Insulation thickness	105 mm
Material of interior	SUS 304
Door	Foamed door, top open
Door handle	Recessed door handle with lock
Baskets	NA
Casters	4 pcs, casters
Net weight	45 kg
Alt Name	-50°C Low temperature chest freezer

APPLICATIONS

The -50°C low temperature chest freezers are used for fresh keeping storage of deep seafood and high grade foods; also for freezing storage of biological samples, products and reagents and low temperature storage of chemical and electronic materials.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com