



-50°C CHEST FREEZER BKD-310

-40°C FREEZER BKD-310

-50°C LOW TEMPERATURE CHEST FREEZER



SPECIFICATIONS

Model	BKD-310
Capacity	558L
Temperature Range	-15°C ~ -50°C
Climate class	T
Unit dimensions	1625*880*950 mm
Interior dimensions	1425*595*705 mm
Power supply	220V/50Hz or 115V/60Hz
Rated input	400 W
Power consumption	consumption 5.20 kW.h/24h (FRO)
Refrigerants	Mixed CFC free refrigerants
Compressor	World Brand compressor
Temperature controller	Brand electronic controller
Temperature display	Digital temperature display
Evaporator	Wall type copper tube evaporator
Condenser	Al finned copper tube condenser
Condensation fan	German brand, EBM fan
Insulation thickness	100 mm
Material of interior	SUS 304
Door	Foamed door, top open
Door handle	Recessed door handle with lock
Baskets	1pc, plastic coated steel wire
Casters	4 pcs, casters
Net weight	115 kg
Alt Name	-50°C Low temperature chest freezer

APPLICATIONS

The -50°C low temperature chest freezers are used for fresh keeping storage of deep seafood and high grade foods; also for freezing storage of biological samples, products and reagents and low temperature storage of chemical and electronic materials.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com